


Conical pole

Last information update: March 2025



Accessory code

1275: Tapered pole H 4600mm D 106-60mm

Technical description

Tapered pole made of 70 micron hot galvanised steel, in compliance with UNI EN ISO 1461 (EN 40-5), subsequently surface treated with acrylic powder paint. The standard painting cycle refers to the UNI EN ISO 12944 standard with durability class C4-H (suitable for industrial areas and coastal zones with moderate salinity). The UNI EN ISO 12944-1 standard specifies routine maintenance and 6-monthly checks to conserve the product intact. The pole consists of a single welded tube made of EN 10025-S235JR (ex Fe 360 UNI 7070) steel, 106 mm in diameter at the base and 60 mm at the top. It is 3 mm thick and 4600 mm long. The slot for the access cover measures 186x45 mm, is at a height of 800 mm from the ground, and is suitable for fitting the terminal block with two fuses (code 1864). External access cover made of GDALSI 12 - EN 1706 AC - 46100 DF die-cast aluminium alloy, with rounded shape and edges; button head fixing screws with a triangular recess with half-rounded sides, made of AISI 304 stainless steel. It comes complete with the relative access cover key (code 0227). A flexible polyvinyl chloride (PVC) gasket adapts to the uneven pole surface to ensure that it is sealed. There is a metal hook for supporting the terminal block inside the pole. It consists of a metal rod, 4 mm in diameter, bent twice, measures 40x21 mm and is welded at a height of approximately 996 mm from the ground. The pole is suitable for withstanding the dynamic wind force, in accordance with the Italian Ministerial Decree of 16/01/96.

Installation

To be buried 600 mm deep.

Colour

Grey (15)

Weight (Kg)

29

Wiring

The access slot (186x45 mm) is closed by a die-cast aluminium cover and is located 800 mm from the ground. The power cable enters through a slot (150x50 mm) on the pole, 100 mm from the end. The pole is earthed through a tropicalised insert to be inserted in the hole, d=11 mm, located 700 mm from the end of the pole.

Notes

When connected appropriately the pole can be Class II

Complies with EN60598-1 and pertinent regulations

