

## Laser Blade


Design iGuzzini

iGuzzini

Last information update: March 2025

### Product configuration: EJ95.D8

EJ95.D8: 5 - cell Recessed luminaire - LED Neutral white - Incorporated DALI dimmable power supply - Wide Flood optic - 12.7W  
972lm - 4000K - CRI 90 - White Transparent



### Product code

EJ95.D8: 5 - cell Recessed luminaire - LED Neutral white - Incorporated DALI dimmable power supply - Wide Flood optic - 12.7W  
972lm - 4000K - CRI 90 - White Transparent

### Technical description

rectangular miniaturised recessed luminaire with 5 optical elements with LED lamps - fixed optics - wide flood beam angle. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare. Supplied with DALI dimmable electronic control gear connected to the luminaire. Neutral white LED

### Installation

recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 141

### Colour

White Transparent (D8)

### Weight (Kg)


0.3

### Mounting

wall recessed|ceiling recessed

### Wiring

on control gear box; screw connections with terminal block included



Complies with EN60598-1 and pertinent regulations



### Technical data

lm system:	1008	CRI (typical):	92
W system:	12.7	Colour temperature [K]:	4000
lm source:	1200	MacAdam Step:	3
W source:	9.9	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	79.4	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	84	Number of optical assemblies:	1
Beam angle [°]:	46°	Control:	DALI-2
CRI (minimum):	90		


### Polar

<p>Imax=1797 cd C90-270 90° 180° 90° 2000 0° α=47°</p>	<b>CIE</b> nL 0.84 96-99-100-100-84 UGR 12.8-13.4 <b>DIN</b> A.61 <b>UTE</b> 0.84A+0.00T F*1=964 F*1+F*2=988 F*1+F*2+F*3=997				
	<b>Lux</b>				
	h	d1	d2	Em	Emax
	2	1.7	1.7	370	449
	4	3.5	3.4	92	112
	6	5.2	5.1	41	50
	8	6.9	6.8	23	28

# Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	70	67	65	70	67	66	64	76
1.0	78	74	71	69	73	71	71	68	81
1.5	82	79	77	75	78	76	76	73	87
2.0	85	83	81	80	82	80	79	77	91
2.5	87	85	84	83	84	83	82	79	94
3.0	88	87	86	85	85	84	83	81	96
4.0	89	88	87	87	87	86	85	83	98
5.0	89	89	88	88	87	87	86	83	99

# Luminance curve limit



# UGR diagram

Corrected UGR values (at 1200 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	11.2	11.7	11.4	11.9	12.2	11.7	12.3	12.0	12.5	12.7
	3H	11.6	12.1	11.9	12.3	12.6	11.8	12.3	12.2	12.6	12.9
	4H	11.8	12.3	12.1	12.6	12.9	11.9	12.3	12.2	12.6	12.9
	6H	12.0	12.4	12.4	12.8	13.1	11.9	12.3	12.2	12.6	12.9
	8H	12.1	12.5	12.5	12.9	13.2	11.8	12.2	12.2	12.6	12.9
	12H	12.3	12.7	12.7	13.0	13.4	11.8	12.2	12.2	12.5	12.9
4H	2H	11.4	11.8	11.7	12.1	12.4	12.7	13.1	13.0	13.4	13.7
	3H	12.0	12.3	12.3	12.7	13.0	13.1	13.5	13.5	13.8	14.2
	4H	12.3	12.7	12.7	13.0	13.4	13.3	13.6	13.7	14.0	14.4
	6H	12.7	13.0	13.1	13.4	13.8	13.4	13.7	13.8	14.1	14.5
	8H	12.8	13.1	13.3	13.5	13.9	13.4	13.7	13.8	14.1	14.5
	12H	13.0	13.3	13.5	13.7	14.2	13.4	13.6	13.8	14.1	14.5
8H	4H	12.5	12.8	13.0	13.2	13.6	13.9	14.1	14.3	14.6	15.0
	6H	13.0	13.2	13.4	13.6	14.1	14.1	14.3	14.6	14.8	15.3
	8H	13.2	13.4	13.7	13.8	14.3	14.2	14.4	14.7	14.9	15.4
	12H	13.5	13.7	14.0	14.2	14.7	14.2	14.4	14.7	14.9	15.4
12H	4H	12.5	12.8	13.0	13.2	13.7	14.0	14.3	14.5	14.7	15.2
	6H	13.0	13.2	13.5	13.7	14.1	14.3	14.5	14.8	15.0	15.5
	8H	13.3	13.4	13.8	13.9	14.4	14.5	14.6	15.0	15.1	15.6
Variations with the observer position at spacing:											
S =		1.0H					1.8 / -1.2				
		1.5H					3.3 / -1.5				
		2.0H					4.8 / -1.8				
							1.3 / -1.1				
							2.7 / -1.3				
							4.1 / -1.6				