



Last information update: July 2024

**Accessory code**

PD28: Module with DALI-2 light and motion multi-sensor - For iN 60 MMO and Space - Frame

Technical description

Module complete with DALI-2 sensor for compatible DALI-2 check systems.

The sensor detects movement (PIR) and the lighting value.

It is powered through the DALI bus (consumption 9 mA).

Dynamic lighting range: 1 - 1000 lx.

Movement detection angle 84°.

Detection angle for light measurement 30° - 60° (asymmetric).

Installation

Recessed installation with iN 60 MMO/Space modules. Assembly height min 2.4 m / max 4 m for movement and max 3 m as a lux + movement sensor. Refer to the instruction sheet for the positions allowed and whether the PD37 accessory is required.

Example of motion coverage diameter: 4.3 m @ h2.4 m installation.

Colour

White (01)

Weight (Kg)

0.39

Wiring

The module is powered by the wiring inside the iN 60 MMO/Space luminaire it is connected to. The sensor and the relative recessed iN 60 MMO/Space luminaires must be controlled by a DALI-2 control system that is compatible with and certified for controlling sensors.

Notes

DALI EN 62386-101 ed.2 (DALI-2) The sensor used is DALI-2 certified parts 101,103,301,303,304

For systems compatible with the DALI-2 sensor, contact iGuzzini.

Complies with EN60598-1 and pertinent regulations



IP20

Technical data

Control: DALI-2