

Last information update: March 2025

**Product configuration: RU37.12+PI22.12**

RU37.12: Linear module - recessed Minimal Down - for MMO/Space/Wall Washer versions - L=3576 - Aluminium

PI22.12: Plate with Warm White LED - MMO Downlight - UGR<19 - LO - DALI - L=1192 - 18.4W 2587.2lm - 3000K - Aluminium

**Product code**

RU37.12: Linear module - recessed Minimal Down - for MMO/Space/Wall Washer versions - L=3576 - Aluminium

**Technical description**

Recessed Minimal (Frameless) version with extruded aluminium profile installed flush with ceiling. Designed for use with an LED plate in MMO, Space and Wall Washer versions.

**Installation**

Can be recess-mounted.


**Colour**

Aluminium (12)

**Wiring**

Designed to house the LED modules that can be used by the system.

Complies with EN60598-1 and pertinent regulations

**Product code**

PI22.12: Plate with Warm White LED - MMO Downlight - UGR<19 - LO - DALI - L=1192 - 18.4W 2587.2lm - 3000K - Aluminium

**Technical description**

Warm White LED plate with direct (Down) emission in an MMO version. Low Output (LO) version with controlled luminance down emission  $L \leq 3000 \text{ cd/m}^2 - \alpha > 65^\circ$ , for use in environments with video monitors (UGR<19) in compliance with EN 12464-1. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. Moulded and metallised polycarbonate raster.

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

Aluminium (12)

**Weight (Kg)**

0.93

**Wiring**

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI power supply.

**Notes**

TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



IP20



pending




pending

**Technical data**

lm system:	7762	Colour temperature [K]:	3000
W system:	55.2	MacAdam Step:	3
lm source:	10080	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	48	Lamp code:	LED
Luminous efficiency (lm/W, real value):	140.6	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	77	Number of optical assemblies:	1
CRI (minimum):	80	Control:	DALI-2


# Polar



# Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	65	60	56	54	59	56	56	53	68
1.0	69	64	61	59	63	61	60	57	74
1.5	74	70	68	66	69	67	67	64	83
2.0	77	74	72	71	73	71	71	68	88
2.5	78	76	75	74	75	74	73	71	92
3.0	79	78	77	76	77	76	75	72	94
4.0	81	79	78	78	78	77	76	74	96
5.0	81	80	79	79	79	78	77	75	97

# Luminance curve limit



# UGR diagram

Corrected UGR values (at 10080 lm bare lamp luminous flux)												
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise					
2H	2H	16.2	16.8	16.5	17.1	17.3	16.0	16.7	16.3	16.9	17.2	17.2
	3H	16.1	16.6	16.4	16.9	17.2	15.9	16.5	16.2	16.8	17.1	17.1
	4H	16.0	16.5	16.3	16.8	17.1	15.9	16.4	16.2	16.7	17.0	17.0
	6H	15.9	16.4	16.3	16.7	17.0	15.8	16.3	16.1	16.6	16.9	16.9
	8H	15.9	16.3	16.2	16.7	17.0	15.7	16.2	16.1	16.5	16.9	16.9
	12H	15.8	16.3	16.2	16.6	17.0	15.7	16.2	16.1	16.5	16.8	16.8
4H	2H	16.0	16.5	16.3	16.8	17.1	15.8	16.4	16.2	16.7	17.0	17.0
	3H	15.9	16.3	16.2	16.6	17.0	15.7	16.2	16.1	16.5	16.8	16.8
	4H	15.8	16.2	16.2	16.5	16.9	15.6	16.0	16.0	16.4	16.8	16.8
	6H	15.7	16.0	16.1	16.4	16.8	15.5	15.9	16.0	16.3	16.7	16.7
	8H	15.6	16.0	16.1	16.4	16.8	15.5	15.8	15.9	16.2	16.7	16.7
	12H	15.6	15.9	16.0	16.3	16.8	15.4	15.7	15.9	16.2	16.6	16.6
8H	4H	15.6	16.0	16.1	16.4	16.8	15.5	15.8	15.9	16.2	16.7	16.7
	6H	15.5	15.8	16.0	16.3	16.7	15.4	15.7	15.9	16.1	16.6	16.6
	8H	15.5	15.7	16.0	16.2	16.7	15.3	15.6	15.8	16.0	16.5	16.5
	12H	15.4	15.6	15.9	16.1	16.6	15.3	15.5	15.8	16.0	16.5	16.5
12H	4H	15.6	15.9	16.0	16.3	16.8	15.4	15.7	15.9	16.2	16.6	16.6
	6H	15.5	15.7	16.0	16.2	16.7	15.3	15.6	15.8	16.0	16.5	16.5
	8H	15.4	15.6	15.9	16.1	16.6	15.3	15.5	15.8	16.0	16.5	16.5
Variations with the observer position at spacing:												
S =		1.0H	3.6 / -10.1				3.6 / -8.7					
		1.5H	5.2 / -22.0				5.1 / -18.4					
		2.0H	7.2 / -22.4				7.1 / -18.5					