

Last information update: November 2024

**Product configuration: Q367+Q409.12**

Q367: Minimal continuous line moduleGeneral Down LightL3594

Q409.12: Plate - General Down Light - Neutral LED - DALI - L 1196 - 4000K - CRI 80 - Aluminium

**Product code**

Q367: Minimal continuous line moduleGeneral Down LightL3594

**Technical description**

Minimal (frameless) version extruded aluminium intermediate profile for flush with ceiling mounting; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Methacrylate opal screen (diffused general light); screen set up for connecting several lengths by overlapping.

**Installation**

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately; mechanical systems for connecting modules included in the package.

**Colour**

White (01) | Aluminium (12)

**Weight (Kg)**

8.5

**Mounting**

ceiling recessed|wall surface|ceiling surface|ceiling pendant

**Wiring**

Set up to house the LED modules required by the system.

**Notes**

Take care with the system configuration. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



IP20

**Product code**

Q409.12: Plate - General Down Light - Neutral LED - DALI - L 1196 - 4000K - CRI 80 - Aluminium

**Technical description**

LED module set up for housing in initial or intermediate system profiles - down emission. DALI dimmable electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Neutral LED.

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

Indeterminate (00)

**Weight (Kg)**

1.37

**Wiring**

Quick coupling terminal block connection to simplify connections between the luminaires. LED module complete with integrated control gear.

Complies with EN60598-1 and pertinent regulations




IP20

**Technical data**

lm system:	11924	CRI (minimum):	80
W system:	120.4	Colour temperature [K]:	4000
lm source:	17800	MacAdam Step:	3
W source:	106	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	99	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	67	Number of optical assemblies:	1

# Polar



# Isolux

