


**Product configuration: Q424+Q451.12**

Q451.12: Plate - Down Office / Working UGR < 19 - Warm LED - L 896 - 12.5W 1368lm - 3000K - Aluminium



Q424: Frame Continuous Line ModuleDown Office / Working UGR < 19L 898

Frame version extruded aluminium intermediate profile with contact frame; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Microprismatic screen for controlled luminance emission UGR < 19 - 3000 cd/m2 (working lighting); screen set up for connecting several lengths by overlapping.

Recessed using the brackets on the profile: the mechanical systems for connecting the modules are included in the package.

Colour	Weight (Kg)
White (01)*   Aluminium (12)*	2.5

\* Colours on request

## ceiling recessed

Set up to house the LED modules required by the system.

Take care with the system configuration. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



Q451.12: Plate - Down Office / Working UGR < 19 - Warm LED - L 896 - 12.5W 1368lm - 3000K - Aluminium **Attention! Code no longer in production**

LED module set up for housing in initial or intermediate system profiles with screen for controlled luminance - down emission. Electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm LED.

Module insertion on profiles facilitated by a quick coupling system.

Colour	Weight (Kg)
Indeterminate (00)   White (01)	1.2


Quick coupling terminal block connection to simplify connections between the luminaires. LED module complete with integrated control gear.

Complies with EN60598-1 and pertinent regulations



Im system:	1368	Colour temperature [K]:	3000
W system:	12.5	MacAdam Step:	3
Im source:	1900	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	10	Voltage [Vin]:	230
Luminous efficiency (lm/W, real value):	109.4	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	72	Number of optical assemblies:	1
CRI (minimum):	80		


Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	54	47	43	40	47	43	42	38	53
1.0	58	52	48	45	51	48	47	43	60
1.5	64	60	56	53	59	56	55	51	71
2.0	68	64	61	59	63	61	60	56	78
2.5	70	67	65	63	66	64	63	60	83
3.0	71	69	67	65	68	66	65	62	86
4.0	73	71	70	68	70	68	67	64	89
5.0	74	72	71	70	71	70	69	66	91

Luminance curve limit



# UGR diagram

Corrected UGR values (at 1900 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise				
2H	2H	15.5	16.5	15.8	16.7	17.0	16.6	17.6	16.9	17.8	18.1
	3H	16.2	17.1	16.6	17.4	17.7	16.8	17.7	17.1	18.0	18.3
	4H	16.6	17.4	16.9	17.7	18.0	16.8	17.7	17.2	18.0	18.3
	6H	16.9	17.6	17.2	17.9	18.3	16.8	17.6	17.2	17.9	18.2
	8H	17.0	17.7	17.3	18.0	18.4	16.8	17.5	17.2	17.9	18.2
	12H	17.0	17.7	17.4	18.1	18.4	16.8	17.5	17.2	17.8	18.2
4H	2H	15.9	16.7	16.3	17.0	17.4	17.5	18.3	17.8	18.6	18.9
	3H	16.8	17.5	17.2	17.8	18.2	17.8	18.5	18.2	18.9	19.2
	4H	17.2	17.8	17.6	18.2	18.6	18.0	18.6	18.4	19.0	19.4
	6H	17.6	18.2	18.1	18.6	19.0	18.1	18.6	18.5	19.0	19.4
	8H	17.8	18.3	18.2	18.7	19.1	18.1	18.6	18.5	19.0	19.4
	12H	17.9	18.3	18.3	18.8	19.2	18.1	18.5	18.5	18.9	19.4
8H	4H	17.4	17.9	17.8	18.3	18.7	18.4	18.9	18.8	19.3	19.7
	6H	17.9	18.3	18.4	18.8	19.3	18.6	19.0	19.0	19.4	19.9
	8H	18.2	18.5	18.6	19.0	19.5	18.7	19.0	19.1	19.5	20.0
	12H	18.3	18.6	18.8	19.1	19.6	18.7	19.0	19.2	19.5	20.0
12H	4H	17.4	17.8	17.8	18.3	18.7	18.4	18.9	18.9	19.3	19.8
	6H	18.0	18.3	18.5	18.8	19.3	18.7	19.0	19.2	19.5	20.0
	8H	18.2	18.5	18.7	19.0	19.5	18.8	19.1	19.3	19.6	20.1
Variations with the observer position at spacing:											
S =		1.0H	0.4 / -0.5		0.3 / -0.4						
		1.5H	0.5 / -1.0		0.7 / -1.2						
		2.0H	1.1 / -1.4		1.6 / -1.6						