

Last information update: November 2024

**Product configuration: QA93+QB15.01**

QA93: Initial moduleMinimal DownGeneral LightL 3596

QB15.01: Down LO plate - DALI - General Light - LED Neutral - L 3588 - 49.5W 5800lm - 4000K - White

**Product code**

QA93: Initial moduleMinimal DownGeneral LightL 3596

**Technical description**

Initial profile in extruded aluminium - Minimal (frameless) version for flush with ceiling mounting and up-down emission; methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

**Installation**

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately. The initial modules can be used individually for various applications if completed with accessory caps and the required LED module - L 3588.

**Colour**

White (01) | Black (04) | Aluminium (12)

**Weight (Kg)**

7

**Mounting**

ceiling recessed|ceiling surface|ceiling pendant

**Wiring**

Set up exclusively to house L 3588 triple-length LED modules.

**Notes**

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



**Product code**

QB15.01: Down LO plate - DALI - General Light - LED Neutral - L 3588 - 49.5W 5800lm - 4000K - White

**Technical description**

LED module set up for housing in intermediate system profiles, ideal for particularly long light lines. Down emission - Low Output version for General Light profiles (with opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Neutral 4000K LED

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

Indeterminate (00)

**Weight (Kg)**

3.8

**Wiring**

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI control gear.

**Notes**

Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.

Complies with EN60598-1 and pertinent regulations



**Technical data**

lm system:	6156	CRI (minimum):	80
W system:	50.1	Colour temperature [K]:	4000
lm source:	8100	MacAdam Step:	3
W source:	45	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	122.9	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1

Polar

