


Last information update: November 2024

Product configuration: QB03

QB03: Angular LED module - Frame Down LO - DALI - General Light - Warm

**Product code**

QB03: Angular LED module - Frame Down LO - DALI - General Light - Warm

Technical description

Angular element for Frame version profiles with contact frame; including a 3000K Warm LED module, Low Output version. Methacrylate opal screen for diffused general light; screen set up for overlap connections. Integrated DALI control gear. Pass-through wiring for continuous lines:

Installation

Recessed using the brackets on the profile.

Colour

White (01)

Weight (Kg)

4.17

Mounting

ceiling recessed

Wiring

The angular profile is supplied with pass-through wiring for continuous lines. Quick coupling terminal blocks to simplify connections between the luminaires. Complete with integrated dimmable digital DALI control gear.

Notes

Take care when configuring the system; to complete a continuous line with an angular profile correctly, two initial modules are required, one for each end of the corner.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



IP20

**Technical data**

lm system:	1900	Colour temperature [K]:	3000
W system:	16.1	MacAdam Step:	3
lm source:	1250	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	7.5	Lamp code:	LED
Luminous efficiency (lm/W, real value):	118	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	2
Light Output Ratio (L.O.R.) [%]:	76	Control:	DALI-2
CRI (minimum):	80		

Polar