

Last information update: November 2024

#### Product configuration: QB15+QZ68.01

QB15: Down LO plate - DALI - General Light - LED Neutral - L 3588

QZ68.01: Module for continuous line - Frame Down - General Light - L 3596 - TP(a) - White

#### Product code

QB15: Down LO plate - DALI - General Light - LED Neutral - L 3588

#### Technical description

LED module set up for housing in intermediate system profiles, ideal for particularly long light lines. Down emission - Low Output version for General Light profiles (with opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Neutral 4000K LED

#### Installation

Module insertion on profiles facilitated by a quick coupling system.

#### Colour

Indeterminate (00)

#### Weight (Kg)

3.8

#### Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI control gear.

#### Notes

Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.

Complies with EN60598-1 and pertinent regulations



#### Product code

QZ68.01: Module for continuous line - Frame Down - General Light - L 3596 - TP(a) - White

#### Technical description

Extruded aluminium intermediate profile - Frame version with contact frame; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Polycarbonate screen for diffused general light in compliance with the TP(a) standard; screen set up for connecting different lengths by overlapping.

#### Installation

This can be recessed using the brackets on the profile; the mechanical systems for connecting the subsequent profiles are included in the package.

#### Colour

White (01)

#### Weight (Kg)

7.4

#### Mounting

ceiling recessed|ceiling pendant


#### Wiring

Set up exclusively to house L 3588 triple-length LED modules.

#### Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

Complies with EN60598-1 and pertinent regulations



#### Technical data

lm system:	5103	CRI (minimum):	80
W system:	45	Colour temperature [K]:	4000
lm source:	8100	MacAdam Step:	3
W source:	45	Lamp code:	LED
Luminous efficiency (lm/W, real value):	113.4	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	63	Control:	DALI-2

Polar

