

Laser Blade


Design iGuzzini

iGuzzini

Last information update: February 2025

Product configuration: QX79.01

QX79.01: Minimal 15 cells - Wide Flood - LED - White



Product code

QX79.01: Minimal 15 cells - Wide Flood - LED - White

Technical description

Linear miniaturised recessed luminaire with 15 optical elements for LED lamps - fixed optic. Die-cast aluminium body, minimal version (frameless) installed flush with ceiling. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Metallised thermoplastic high definition OptiBeam reflector, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare. Supplied with a dimmable DALI power supply unit connected to the luminaire.

Installation

The recess body is inserted in the specific adapter installed previously by means of a steel wire spring - check the thickness of the false ceiling and use a compatible frame available with a separate item code.

Colour

White (01)

Weight (Kg)

0.86

Mounting

wall recessed|ceiling recessed

Wiring

Quick-coupling connections on the ballast unit.


Complies with EN60598-1 and pertinent regulations



IP20

IP23

On the visible part of the product once installed



Technical data

lm system:	2916	CRI (typical):	92
W system:	33.6	Colour temperature [K]:	4000
lm source:	3600	MacAdam Step:	3
W source:	30	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	86.8	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	81	Number of optical assemblies:	1
Beam angle [°]:	47° / 46°	Control:	DALI-2
CRI (minimum):	90		

Polar

	CIE			
	nL 0.81			
	100-100-100-100-81			
	UGR <10-10			
	DIN A.61			
	UTE			
	0.81A+0.00T			
	F*1=1000			
	F*1+F*2=1000			
	F*1+F*2+F*3=1000			
	CIBSE			
	LG3 L<1500 cd/m² at 65°			
	UGR<10 L<1500 cd/mq @65°			
	Lux			
	h	d	Em	E _{max}
	2	1.7	1135	1396
	4	3.5	284	349
	6	5.2	126	155
	8	7	71	87

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	73	70	67	65	69	66	66	64	78
1.0	76	73	71	69	72	70	70	67	83
1.5	80	78	76	74	77	75	74	72	89
2.0	83	81	79	78	80	78	78	75	93
2.5	84	83	82	81	82	81	80	78	96
3.0	85	84	83	83	83	82	81	79	98
4.0	86	85	85	84	84	84	82	81	99
5.0	87	86	86	86	85	84	83	81	100

UGR diagram

Corrected UGR values (at 3000 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	1.0	1.5	1.3	1.7	2.0	1.0	1.5	1.3	1.7	2.0
	3H	0.9	1.3	1.2	1.6	1.9	0.9	1.3	1.2	1.6	1.9
	4H	0.8	1.2	1.1	1.5	1.8	0.8	1.2	1.1	1.5	1.8
	6H	0.7	1.1	1.1	1.4	1.7	0.7	1.1	1.1	1.4	1.7
	8H	0.7	1.1	1.1	1.4	1.7	0.7	1.1	1.1	1.4	1.7
	12H	0.7	1.0	1.0	1.3	1.7	0.7	1.0	1.0	1.3	1.7
4H	2H	0.8	1.2	1.1	1.5	1.8	0.8	1.2	1.1	1.5	1.8
	3H	0.7	1.0	1.0	1.3	1.7	0.7	1.0	1.0	1.3	1.7
	4H	0.6	0.9	1.0	1.2	1.6	0.6	0.9	1.0	1.2	1.6
	6H	0.5	0.8	0.9	1.1	1.6	0.5	0.8	0.9	1.1	1.6
	8H	0.4	0.7	0.9	1.1	1.5	0.4	0.7	0.9	1.1	1.5
	12H	0.4	0.6	0.8	1.0	1.5	0.4	0.6	0.8	1.0	1.5
8H	4H	0.4	0.7	0.9	1.1	1.5	0.4	0.7	0.9	1.1	1.5
	6H	0.3	0.5	0.8	1.0	1.5	0.3	0.5	0.8	1.0	1.5
	8H	0.3	0.5	0.8	0.9	1.4	0.3	0.5	0.8	0.9	1.4
	12H	0.2	0.4	0.7	0.9	1.4	0.2	0.4	0.7	0.9	1.4
12H	4H	0.4	0.6	0.8	1.0	1.5	0.4	0.6	0.8	1.0	1.5
	6H	0.3	0.5	0.8	0.9	1.4	0.3	0.5	0.8	0.9	1.4
	8H	0.2	0.4	0.7	0.9	1.4	0.2	0.4	0.7	0.9	1.4
Variations with the observer position at spacing:											
S =		1.0H	6.8 / -21.9				6.8 / -21.9				
		1.5H	9.7 / -22.0				9.7 / -22.0				
		2.0H	11.7 / -22.2				11.7 / -22.2				