



Last information update: October 2024

**Product configuration: QI75**

QI75: Ceiling-mounted linear GL Pro - 10 cells



**Product code**

QI75: Ceiling-mounted linear GL Pro - 10 cells

**Technical description**

Ceiling-mounted luminaire with 10 optical elements for LED lamps - fixed optics with metallised thermoplastic high definition Opti-Beam reflectors. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient luminous flux optimised by a special diffuser screen that reduces direct glare significantly. Extruded aluminium main body and technical dissipation unit - shaped steel fixing plate. DALI dimmable electronic driver integrated in luminaire body.

**Installation**

Ceiling-mounted with surface fixing plate (screws and screw anchors not included) - external locking system.

**Colour**

White (01) | Black/white (F2)

**Weight (Kg)**

0.69

**Mounting**

ceiling surface

**Wiring**

Cables supplied with quick-coupling terminals for connecting to power supply line.


Complies with EN60598-1 and pertinent regulations



**Technical data**

lm system:	1242	Voltage [Vin]:	230
W system:	22.8	Lamp code:	LED
lm source:	1800	Number of lamps for optical assembly:	1
W source:	20	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	54.5	Number of optical assemblies:	1
lm in emergency mode:	-	Power factor:	See installation instructions
Total light flux at or above an angle of 90° [Lm]:	0	Inrush current:	5 A / 50 µs
Light Output Ratio (L.O.R.) [%]:	69	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 31 luminaires B16A: 50 luminaires C10A: 52 luminaires C16A: 85 luminaires
CRI (minimum):	90	Minimum dimming %:	1
Colour temperature [K]:	2700	Overvoltage protection:	4kV Common mode & 2kV Differential mode
MacAdam Step:	2	Control:	DALI-2
Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)		


**Polar**



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	58	54	51	49	54	51	51	48	69
1.0	62	58	55	53	57	55	54	52	75
1.5	66	63	61	59	62	60	60	57	83
2.0	69	66	65	63	65	64	63	61	88
2.5	70	68	67	66	67	66	65	63	92
3.0	71	70	69	68	69	68	67	65	94
4.0	72	71	70	70	70	69	68	66	96
5.0	73	72	71	71	71	70	69	67	97

Luminance curve limit



UGR diagram

Corrected UGR values (at 1800 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	21.8	22.5	22.1	22.7	22.9	21.8	22.5	22.1	22.7	22.9
	3H	21.8	22.4	22.1	22.6	22.9	21.8	22.4	22.1	22.7	23.0
	4H	21.8	22.3	22.1	22.6	22.9	21.8	22.3	22.1	22.6	22.9
	6H	21.8	22.3	22.1	22.6	22.9	21.7	22.2	22.1	22.5	22.8
	8H	21.8	22.2	22.1	22.6	22.9	21.7	22.2	22.0	22.5	22.8
	12H	21.7	22.2	22.1	22.5	22.9	21.6	22.1	22.0	22.4	22.8
4H	2H	21.8	22.3	22.1	22.6	22.9	21.8	22.3	22.1	22.6	22.9
	3H	21.8	22.2	22.2	22.6	22.9	21.8	22.3	22.2	22.6	23.0
	4H	21.8	22.2	22.2	22.6	22.9	21.8	22.2	22.2	22.6	22.9
	6H	21.8	22.1	22.2	22.5	23.0	21.7	22.1	22.2	22.5	22.9
	8H	21.8	22.1	22.2	22.5	23.0	21.7	22.0	22.1	22.4	22.9
	12H	21.8	22.1	22.2	22.5	23.0	21.7	22.0	22.1	22.4	22.8
8H	4H	21.7	22.0	22.1	22.4	22.9	21.8	22.1	22.2	22.5	23.0
	6H	21.7	22.0	22.2	22.5	22.9	21.8	22.0	22.2	22.5	23.0
	8H	21.8	22.0	22.2	22.4	22.9	21.8	22.0	22.2	22.4	22.9
	12H	21.8	22.0	22.3	22.4	23.0	21.7	21.9	22.2	22.4	22.9
12H	4H	21.7	22.0	22.1	22.4	22.8	21.8	22.1	22.2	22.5	23.0
	6H	21.7	21.9	22.2	22.4	22.9	21.8	22.0	22.2	22.5	23.0
	8H	21.7	21.9	22.2	22.4	22.9	21.8	22.0	22.3	22.4	23.0
Variations with the observer position at spacing:											
S =	1.0H	2.4 / -2.2					2.4 / -2.2				
	1.5H	4.5 / -4.7					4.5 / -4.7				
	2.0H	6.3 / -6.0					6.3 / -6.0				