


Last information update: May 2024

**Product configuration: 5236**

5236: Ceiling luminaire with inductive control gear 2x18W TC-L

**Product code**5236: Ceiling luminaire with inductive control gear 2x18W TC-L **Attention! Code no longer in production****Technical description**

Luminaire for internal lighting designed for use with circular fluorescent lamps TC-L 2x18W. It is made from a drawn sheet-metal plate and supports the wiring for fluorescent lamps, the terminal board and the lampholders. To the same plate is fixed a methacrylate screen by rotating the spring situated along the perimeter of the fitting.

**Installation**

Fixed to the wall or the ceiling with fischer screws.

**Colour**

White (01)

**Weight (Kg)**

2

**Mounting**

wall surface|ceiling surface

**Wiring**

Directly connected to the 230 V mains supply.

Complies with EN60598-1 and pertinent regulations



650°C

IP40

**Technical data**

|  |         |                                       |      |
|--|---------|---------------------------------------|------|
| lm system:   | 1430.16 | CRI:                                  | 85   |
| W system:  | 42.0    | Colour temperature [K]:               | 4000 |
| lm source:   | 2400    | Voltage [Vin]:                        | 230  |
| W source:  | 18      | Lamp code:                            | 1771 |
| Luminous efficiency (lm/W, real value):            | 34.05   | Socket:                               | 2G11 |
| lm in emergency mode:                              | -       | Number of lamps for optical assembly: | 2    |
| Total light flux at or above an angle of 90° [Lm]: | 2.15    | ZVEI Code:                            | TC-L |
| Light Output Ratio (L.O.R.) [%]:                   | 60      | Number of optical assemblies:         | 1    |
| Beam angle [°]:                                    | 122°    |                                       |      |