iGuzzini

Last information update: October 2024

## Product configuration: P871

P871: Pole-mounted system - Small body optical assembly - Warm White - ST1 street optic.




## Product code P871: Pole-mounted system - Small body optical assembly - Warm White - ST1 street optic. Technical description Outdoor luminate with direct light street optic, designed to use LED lamps. The optical asse

Outdoor luminaire with direct light street optic, designed to use LED lamps. The optical assembly is made of EN1706AC 46100LF aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and an acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. With a 5 mm thick tempered sodium-calcium glass cover. When pole-mounted the product can be adjusted by +15°/-5° and +5°/-15 when side-mounted. High visual comfort. Polymer optic lenses offering high yield and even light distribution. Complete with circuit fitted with Warm White monochrome power LEDs. Extractable control gear connected with quick-coupling connectors. 220-240V ac 50/60Hz DALI electronic ballast. The optical assembly is fixed to the ceiling or pole-top attachment by two fixing screws. The light flow emitted in the upper hemisphere of the system in the horizontal position is null (in conformity with the strictest standards for the prevention of light pollution). All external screws are made of stainless steel.

The floodlight can be installed on the pole-top with a die-cast aluminium single/double attachment for ø60/76/102/120mm poles or a triple attachment for ø102/120 mm poles. Side die-cast aluminium attachment for tapered poles with diameters between ø 46 and

Weight (Kg)

4.72





214

## Mounting

Colour

. ø76.

Installation

## wall arm|pole arm|pole-top side entry|pole-top

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

Wiring

The product is connected by inserting the mains cables in a push in terminal board. Resistance to mains voltage spikes of up to 10KV. Product perfect watertightness at the power cable entry point is guaranteed by a nickel-plated brass M24x1.5 cable clamp, suitable for cables with a max external 14mm  $\emptyset$  (1,5-2.5mm<sup>2</sup> cross section).

							Co	Complies with EN60598-1 and pertinent regulations				
	IK08	IP66	C€	UK	Æ13	8	EAC		<u>1004</u> (3)	W	©	
<u>(B</u> )												

Technical data					
Im system:	3780	Life Time LED 2:	100,000h - L90 - B10 (Ta 40°C)		
W system:	33	Lamp code:	LED		
Im source:	-	Number of lamps for optical	1		
W source:	-	assembly:			
Luminous efficiency (Im/W,	114.5	ZVEI Code:	LED		
real value):		Number of optical	1		
Im in emergency mode:	-	assemblies:			
Total light flux at or above	0	Intervallo temperatura	from -40°C to 50°C.		
an angle of 90° [Lm]:		ambiente:			
Light Output Ratio (L.O.R.)	100	Power factor:	See installation instructions		
[%]:		Inrush current:	31 A / 186 μs		
CRI (minimum):	70	Maximum number of	B10A: 18 luminaires B16A: 30 luminaires C10A: 31 luminaires C16A: 51 luminaires		
Colour temperature [K]:	3000	luminaires of this type per			
MacAdam Step:	3	miniature circuit breaker:			
Life Time LED 1:	100,000h - L90 - B10 (Ta 25°C)				
		Minimum dimming %:	10		
		Overvoltage protection:	10kV Common mode & 6kV Differential mode		
		Control:	DALI-2		

