


Last information update: May 2024

**Product configuration: BU79**

BU79: Spotlight with base - Warm White COB LED - Integrated electronic control gear - Spot optic

**Product code**BU79: Spotlight with base - Warm White COB LED - Integrated electronic control gear - Spot optic **Attention! Code no longer in production****Technical description**

Spotlight designed to use LED lamps and a spot optic. Consists of an optical assembly and a base. The optical assembly, arm, base and frame holder are made of EN1706AC 46100LF aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The next painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The 4 mm thick, tempered, sodium-calcium, closing glass is colourless, transparent and secured with captive screws. The 50/60 Shore A silicone seal has been subject to post-cooling treatment, in an oven, for 4-6 hours at 200 °C. The optical assembly allows vertical and horizontal adjustments, with the possibility of locking the adjustment for aiming, and it has slots in the frame for rainwater drainage. Optic with a metalized-coated polycarbonate reflector. Complete with Warm White colour monochrome LED circuit. The cable gland for connecting the wiring assembly to the lamp assembly is made of nickel-plated brass M14x1. For the power supply, the device is fitted with a black polyamide PG11 cable gland, suitable for 6.5 to 11.5 mm cables. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN60598-1 standards and particular requirements.

**Installation**

The luminaire can be floor, ceiling or wall-mounted using either screw anchors for concrete, cement and solid brick or various other available accessories.

**Colour**

Black (04) | Grey (15)

**Weight (Kg)**

0.9

**Mounting**

wall arm|ground surface|wall surface|ground anchored|ground spike|ceiling surface

**Wiring**

Control gear complete with electronic ballast (220÷240Vac 50/60Hz)

Complies with EN60598-1 and pertinent regulations


**Technical data**

Im system:	585	Colour temperature [K]:	3000
W system:	10.2	MacAdam Step:	3
Im source:	790	Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)
W source:	8	Life Time LED 2:	50,000h - L80 - B10 (Ta 40°C)
Luminous efficiency (Im/W, real value):	57.3	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	74	Number of optical assemblies:	1
Beam angle [°]:	12°	Intervallo temperatura ambiente:	from -20°C to +35°C.
CRI (minimum):	80		

**Polar**

Imax=4360 cd		Lux			
90°	180°	90°	h	d	Em Emax
			4	0.8	212 273
			8	1.7	53 68
			12	2.5	24 30
			16	3.4	13 17
$\alpha = 12^\circ$					

### Isolux



### UGR diagram

Corrected UGR values (at 790 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	20.0	21.6	20.4	21.9	22.2	20.0	21.6	20.4	21.9	22.2
	3H	19.9	21.0	20.3	21.3	21.6	19.9	21.0	20.3	21.3	21.6
	4H	19.8	20.8	20.2	21.1	21.4	19.8	20.8	20.2	21.1	21.5
	6H	19.7	20.7	20.1	21.0	21.4	19.7	20.7	20.1	21.0	21.4
	8H	19.7	20.7	20.1	21.0	21.4	19.7	20.7	20.1	21.0	21.4
	12H	19.6	20.6	20.0	21.0	21.4	19.6	20.6	20.0	21.0	21.4
4H	2H	19.8	20.8	20.2	21.1	21.5	19.8	20.8	20.2	21.1	21.4
	3H	19.6	20.6	20.0	21.0	21.4	19.6	20.6	20.0	21.0	21.4
	4H	19.5	20.6	19.9	21.0	21.4	19.5	20.6	19.9	21.0	21.4
	6H	19.3	20.6	19.7	21.0	21.5	19.3	20.6	19.7	21.0	21.5
	8H	19.2	20.6	19.6	21.0	21.5	19.2	20.6	19.6	21.0	21.5
	12H	19.0	20.6	19.5	21.0	21.5	19.0	20.6	19.5	21.0	21.5
8H	4H	19.2	20.6	19.6	21.0	21.5	19.2	20.6	19.6	21.0	21.5
	6H	19.0	20.4	19.5	20.9	21.4	19.0	20.4	19.5	20.9	21.4
	8H	19.0	20.2	19.6	20.7	21.2	19.0	20.2	19.6	20.7	21.2
	12H	19.1	19.9	19.6	20.4	20.9	19.1	19.9	19.6	20.4	20.9
12H	4H	19.0	20.6	19.5	21.0	21.5	19.0	20.6	19.5	21.0	21.5
	6H	19.0	20.2	19.6	20.7	21.2	19.0	20.2	19.6	20.7	21.2
	8H	19.1	19.9	19.6	20.4	20.9	19.1	19.9	19.6	20.4	20.9
Variations with the observer position at spacing:											
S =		1.0H	3.6 / -9.8				3.6 / -9.8				
		1.5H	6.0 / -15.5				6.0 / -15.5				
		2.0H	8.0 / -17.5				8.0 / -17.5				