iGuzzini

Last information update: May 2024

#### Product configuration: E987 E987: Underscore InOut



# E987: Underscore InOut Attention! Code no longer in production

Colour

Product code


White (01)

## Mounting wall arm|wall surface|ceiling surface

# Notes

Underscore InOut can be powered in series up to a maximum length of L=7004mm. The product is not suitable for installation in swimming pools and fountains. The lengths indicated can have a tolerance of +/-4mm compared to the nominal length.





Technical data			
Im system:	70	Life Time LED 1:	50,000h - L70 - B20 (Ta 25°C)
W system:	2.1	Life Time LED 2:	30,000h - L70 - B20 (Ta 40°C)
Im source:	70	Voltage [Vin]:	24
W source:	2.1	Lamp code:	LED
Luminous efficiency (lm/W, real value):	33.3	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	18	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	100	Intervallo temperatura ambiente:	from -30°C to 45°C.
CRI (minimum):	80	LED current [mA]:	18
Colour temperature [K]:	2500	Control:	PWM
MacAdam Step:	3		

### Polar

