


Last information update: May 2024

Product configuration: QB06

QB06: Angular LED module - Minimal Down LO - ON-OFF - General Light - Warm

**Product code**QB06: Angular LED module - Minimal Down LO - ON-OFF - General Light - Warm **Attention! Code no longer in production****Technical description**

Angular element for Minimal (frameless) flush with ceiling version profiles; including a 3000K Warm LED module Low Output version. Methacrylate opal screen for diffused general light; screen set up for overlap connections. Integrated control gear. Pass-through wiring for continuous lines:

Installation

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately.

Colour

White (01) | Black (04) | Aluminium (12)

Weight (Kg)

4.17

Mounting

ceiling recessed|ceiling surface|ceiling pendant

Wiring

The angular profile is supplied with pass-through wiring for continuous lines. Quick coupling terminal blocks to simplify connections between the luminaires. LED module complete with integrated ON-OFF non-dimmable control gear.

Notes

Important: the Minimal angular module is only available for Down emission. Take care when configuring the system; to complete a continuous line with an angular profile correctly, two initial modules are required, one for each end of the corner.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	1900	CRI (minimum):	80
W system:	17.1	Colour temperature [K]:	3000
Im source:	1250	MacAdam Step:	3
W source:	7.5	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	111.1	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	2

Polar