


Last information update: February 2025

Product configuration: RB31

RB31: 2 - cell Recessed luminaire - LED - Warm white Flood



Product code

RB31: 2 - cell Recessed luminaire - LED - Warm white Flood

Technical description

rectangular miniaturised recessed luminaire with 2 optical elements with LED lamps - fixed optics - flood beam angle. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen. Connecting cable supplied. Ballast not included, available with separate code. Warm white LED.

Installation

recessed with steel wire springs for false ceilings from 1 to 20 mm thick - preparation hole 35 x 64

Colour

White (01) | Black / Black (43) | Black / White (47) | White/Gold (41)* | Grey / Black (74)* | White / burnished chrome (E7)*

Weight (Kg)

0.09

* Colours on request

Mounting

wall recessed|ceiling recessed

Wiring

direct current ballasts to be ordered separately: electronic (MXF9) for max. 7 LEDs; DALI dimmable (BZM4) for max. 20 LEDs (check instruction leaflet for compatible lengths of cables to be used)


Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	391	CRI (typical):	92
W system:	4	Colour temperature [K]:	3500
Im source:	460	MacAdam Step:	3
W source:	4	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	97.8	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	85	Number of optical assemblies:	1
Beam angle [°]:	32°	LED current [mA]:	700
CRI (minimum):	90		

Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	77	73	70	68	72	70	69	67	78
1.0	80	77	74	72	76	74	73	71	83
1.5	84	81	79	78	80	79	78	75	89
2.0	87	85	83	82	84	82	81	79	93
2.5	88	87	86	85	86	85	84	81	96
3.0	89	88	88	87	87	86	85	83	98
4.0	90	90	89	89	88	88	87	84	99
5.0	91	90	90	90	89	89	87	85	100

UGR diagram

Corrected UGR values (at 400 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	-2.7	-2.1	-2.4	-1.9	-1.7	-2.7	-2.1	-2.4	-1.9	-1.7
	3H	-2.8	-2.3	-2.5	-2.1	-1.8	-2.8	-2.3	-2.5	-2.1	-1.8
	4H	-2.9	-2.4	-2.6	-2.1	-1.9	-2.9	-2.4	-2.6	-2.1	-1.9
	6H	-3.0	-2.5	-2.6	-2.2	-1.9	-3.0	-2.5	-2.6	-2.2	-1.9
	8H	-3.0	-2.6	-2.6	-2.3	-1.9	-3.0	-2.6	-2.6	-2.3	-1.9
	12H	-3.0	-2.7	-2.7	-2.3	-2.0	-3.0	-2.7	-2.7	-2.3	-2.0
4H	2H	-2.9	-2.4	-2.6	-2.1	-1.9	-2.9	-2.4	-2.6	-2.1	-1.9
	3H	-3.0	-2.7	-2.7	-2.3	-2.0	-3.0	-2.7	-2.7	-2.3	-2.0
	4H	-3.1	-2.8	-2.7	-2.4	-2.0	-3.1	-2.8	-2.7	-2.4	-2.0
	6H	-3.2	-2.9	-2.8	-2.5	-2.1	-3.2	-2.9	-2.8	-2.5	-2.1
	8H	-3.3	-3.0	-2.8	-2.6	-2.1	-3.3	-3.0	-2.8	-2.6	-2.1
	12H	-3.3	-3.1	-2.9	-2.6	-2.2	-3.3	-3.1	-2.9	-2.6	-2.2
8H	4H	-3.3	-3.0	-2.8	-2.6	-2.1	-3.3	-3.0	-2.8	-2.6	-2.1
	6H	-3.4	-3.1	-2.9	-2.7	-2.2	-3.4	-3.1	-2.9	-2.7	-2.2
	8H	-3.4	-3.2	-2.9	-2.8	-2.3	-3.4	-3.2	-2.9	-2.8	-2.3
	12H	-3.5	-3.3	-3.0	-2.8	-2.3	-3.5	-3.3	-3.0	-2.8	-2.3
12H	4H	-3.3	-3.1	-2.9	-2.6	-2.2	-3.3	-3.1	-2.9	-2.6	-2.2
	6H	-3.4	-3.2	-2.9	-2.8	-2.3	-3.4	-3.2	-2.9	-2.8	-2.3
	8H	-3.5	-3.3	-3.0	-2.8	-2.3	-3.5	-3.3	-3.0	-2.8	-2.3
Variations with the observer position at spacing:											
S =	1.0H	0.9 / -25.5					0.9 / -25.5				
	1.5H	9.7 / -26.0					9.7 / -26.0				
	2.0H	11.7 / -26.8					11.7 / -26.8				