


Last information update: December 2024

Product configuration: Q393

Q393: Minimal Angular Module - General Down Light - Neutral LED - DALI

**Product code**

Q393: Minimal Angular Module - General Down Light - Neutral LED - DALI

Technical description

Angular element for Minimal (frameless) flush with ceiling version profiles; including a Neutral LED module. Methacrylate opal screen (diffused general light); screen set up for connecting several lengths by overlapping. Built-in DALI dimmable control gear. Pass-through wiring for continuous lines:

Installation

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately.

Colour

White (01) | Aluminium (12)

Weight (Kg)

5

Mounting

ceiling recessed|ceiling surface|ceiling pendant

Wiring

The angular profile is supplied with pass-through wiring for continuous lines. Quick coupling terminal blocks to simplify connections between the luminaires. LED module complete with integrated dimmable DALI control gear.

Notes

Take care when configuring the system; to complete a continuous line with an angular profile correctly, two initial modules are required, one for each side of the corner.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	3996	Colour temperature [K]:	4000
W system:	33	MacAdam Step:	3
lm source:	2700	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	15	Voltage [Vin]:	230
Luminous efficiency (lm/W, real value):	121.1	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	74	Number of optical assemblies:	2
CRI (minimum):	80	Control:	DALI-2

Polar

	Lux				
	h	d1	d2	Em	Emax
	2	4.9	5.1	115	192
	4	9.8	10.2	29	48
	6	14.7	15.4	13	21
	8	19.6	20.5	7	12

Isolux

