Le Perroquet

Design Piano Design **iGuzzini**

Last information update: March 2025

Product code
035C: LV Ø80 Spot projector for Filorail - Optibeam Lens - DALI Powerline

Technical description
Miniaturised adjustable spotlight with adapter for installation on a 48V Filorail low voltage track. High yield LED lamp with high color rendering index. DC/DC driver circuit with dimmable DALI function integrated in the body. The Dali «power line» technology allows each spotlight on the track to be adjusted separately. Luminaire body made of die-cast aluminium and thermoplastic material. Swivel joints allow the spotlight to be rotated by 360° about the vertical axis and tilted by 90° tilting relative to the horizontal plane. The set back position of the optic unit guarantees a high level of visual comfort. High definition lens in thermoplastic material. Mechanical aiming locks fitted on both the spotlight and adapter allow rotation and tilting movements to be locked in position to ensure efficient light aiming even after the original installation or during maintenance. The optical assembly is equipped with an accessory holding ring designed to contain a flat accessory.

Installation
Installation on a Filorail track.



Colour
White (01) | Orange (02) | Black (04) | Red (05) | Yellow (06) | Sky blue (09)

Mounting
Low voltage track

Wiring
LED driver integrated in product body - direct connection on 48V track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations

pending

Technical data

lm system:	1074 (*)	CRI:	90
W system:	13.5 (*)	Colour temperature [K]:	3000
lm source:	-	Number of lamps for optical assembly:	1
W source:	-	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	78 (*)	Number of optical assemblies:	1
lm in emergency mode:	-	Control:	DALI
Beam angle [°]:	28 (*)		