



Last information update: May 2024

Product configuration: 5235

5235: Ceiling luminaire with inductive control gear 2x9W TC

**Product code**5235: Ceiling luminaire with inductive control gear 2x9W TC **Attention! Code no longer in production****Technical description**

Luminaire for internal lighting using TC 2x9W compact fluorescent lamps. It is made up of a drawn sheet-metal plate and supports the control gear for fluorescent lamps, the terminal block and the lamp holders. A methacrylate screen is applied on the same plate by rotating the springs located along the perimeter of the luminaire.

Installation

Fixed to the wall or the ceiling with fischer screws.

Colour

White (01)

Weight (Kg)

0.95

Mounting

wall surface|ceiling surface

Wiring

Directly connected to the 230 V mains supply.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	560.4	CRI:	82
W system:	20.0	Colour temperature [K]:	2700
lm source:	1200	Voltage [Vin]:	230
W source:	9	Lamp code:	1729
Luminous efficiency (lm/W, real value):	28.02	Socket:	G23
lm in emergency mode:	-	Number of lamps for optical assembly:	2
Total light flux at or above an angle of 90° [Lm]:	0.84	ZVEI Code:	TC-S
Light Output Ratio (L.O.R.) [%]:	47	Number of optical assemblies:	1
Beam angle [°]:	122°		