


Last information update: April 2024

Product configuration: Q394+PLAF

Q394: Minimal Angular Module - General Down Light - Warm LED

PLAF: Ceiling-mounted luminaire

**Product code**Q394: Minimal Angular Module - General Down Light - Warm LED **Attention! Code no longer in production****Technical description**

Angular element for Minimal (frameless) flush with ceiling version profiles; including a Warm LED module. Methacrylate opal screen (diffused general light); screen set up for connecting several lengths by overlapping. Integrated control gear. Pass-through wiring for continuous lines:

Installation

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately.

Colour

White (01) | Aluminium (12)

Weight (Kg)

5

Mounting

ceiling recessed|ceiling surface|ceiling pendant

Wiring

The angular profile is supplied with pass-through wiring for continuous lines. Quick coupling terminal blocks to simplify connections between the luminaires. LED module complete with integrated electronic control gear.

Notes

Take care when configuring the system; to complete a continuous line with an angular profile correctly, two initial modules are required, one for each side of the corner.

Complies with EN60598-1 and pertinent regulations



IP20

**Technical data**

lm system:	3700	Colour temperature [K]:	3000
W system:	34.5	MacAdam Step:	3
lm source:	2500	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	15	Voltage [Vin]:	230
Luminous efficiency (lm/W, real value):	107.2	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	74	Number of optical assemblies:	2
CRI (minimum):	80		

Polar

Imax=712 cd C0-180		Lux				
90°	180°	90°	h	d1	d2	Em Emax
			2	4.9	5.1	106 178
			4	9.9	10.2	27 45
			6	14.8	15.4	12 20
			8	19.8	20.5	7 11
$\alpha = 102^\circ / 104^\circ$						

Isolux

