

# Constant current power supply unit non dimmable IP20 15W - VIN = 220-240VAC 50/60Hz Iout =350mA

Design iGuzzini

iGuzzini

Last information update: September 2023

## Accessory code

X636: Constant current power supply unit non dimmable IP20 15W - VIN = 220-240VAC 50/60Hz Iout =350mA



## Technical description

Constant current non-dimmable electronic ballast I=350 mA 15 W. Input Vin=220±240 Vac 50÷60 Hz. SELV output. The product features include overvoltage protection, short circuit protection, overcurrent and overtemperature protection. Usage temperature: - 25°C / +45°C.

## Installation

Positioned on top of or inside electrical boxes. Fitted with slots for fastening with screws, if required.

Colour	Weight (Kg)	Dimension (mm) (*)
Indeterminate (00)	0.15	147x44x22

\* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.


## Wiring

Input and output terminals on opposite sides (cable cross-section up to 1.5 mm<sup>2</sup>).  
Primary and secondary cable clamp for cables with a diameter of min. 3 mm - max. 10 mm.

## Notes

SELV, EL

Complies with EN60598-1 and pertinent regulations



## Technical data

Frequency [Hz]:	50/60	Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 31 power supply units
Current out [mA]:	350		B16A: 50 power supply units
Inrush current:	5 A / 50 µs		C10A: 52 power supply units C16A: 85 power supply units
		Overvoltage protection:	4kV Common mode & 2kV Differential mode