

## iN60 Evo Stand-alone

Design iGuzzini

iGuzzini

Last information update: February 2025

### Product configuration: RZ19.L2

RZ19.L2: Pendant-mounted Stand Alone - Neutral White LED - Up/Down - DALI - UGR<19 - LO - MPO - L=2400 - 27.2W 3830.4lm - 4000K - White / Opal White



### Product code

RZ19.L2: Pendant-mounted Stand Alone - Neutral White LED - Up/Down - DALI - UGR<19 - LO - MPO - L=2400 - 27.2W 3830.4lm - 4000K - White / Opal White

### Technical description

Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. Neutral White LED plate with direct (Down) and indirect (Up) light emission. Low Output (LO) controlled luminance version ( $L \leq 3000 \text{ cd/m}^2$ ) ideal for environments with video monitors. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Microprismatic PMMA diffuser screen. Pendant and power supply cables L=1500


### Installation

Pendant-mounted

### Colour

White / Opal White (L2)

Complies with EN60598-1 and pertinent regulations



### Technical data

lm system:	3830	Colour temperature [K]:	4000
W system:	27.2	MacAdam Step:	3
lm source:	5320	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	23	Lamp code:	LED
Luminous efficiency (lm/W, real value):	140.8	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	1886	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	72	Control:	DALI-2
CRI (minimum):	80		

### Polar

