

Last information update: February 2025

**Product configuration: R307.01**

R307.01: body Ø 92 mm - flood optic - 28W 2826lm - 3000K - CRI 90 - White



**Product code**

R307.01: body Ø 92 mm - flood optic - 28W 2826lm - 3000K - CRI 90 - White

**Technical description**

Adjustable spotlight with adapter for installation on a mains voltage track. Luminaire made of die-cast aluminium. Spotlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Built-in dimmable DALI ballast. Luminaire complete with C.O.B. technology LED unit in warm white colour 3000K. Anti-scratch reflector made of P.V.D (physical vapour deposition) aluminium that can provide optimum performance in terms of light efficiency. Flood optic. Possibility of installing a flat accessory, like a glass cover or an elliptical distribution refractor. Interchangeable reflectors that can be ordered as an accessory.

**Installation**

On an electrified track or special base

**Colour**

White (01)

**Weight (Kg)**

0.78


**Mounting**

three circuit track

**Wiring**

Product complete with DALI components


Complies with EN60598-1 and pertinent regulations




**Technical data**

lm system:	2826	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W system:	28	Lamp code:	LED
lm source:	3140	Number of lamps for optical assembly:	1
W source:	24	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	100.9	Number of optical assemblies:	1
lm in emergency mode:	-	Power factor:	See installation instructions
Total light flux at or above an angle of 90° [Lm]:	0	Inrush current:	5 A / 50 µs
Light Output Ratio (L.O.R.) [%]:	90	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 31 luminaires B16A: 50 luminaires C10A: 52 luminaires C16A: 85 luminaires
Beam angle [°]:	29°	Minimum dimming %:	1
CRI (minimum):	90	Overvoltage protection:	4kV Common mode & 2kV Differential mode
Colour temperature [K]:	3000	Control:	DALI-2
MacAdam Step:	2		

**Polar**



### Isolux



### UGR diagram

Corrected UGR values (at 3140 lm bare lamp luminous flux)											
Riflect.:		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
ceiling/cav											
walls											
work pl.											
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	0.5	7.0	6.8	7.3	7.5	6.1	6.6	6.3	6.8	7.0
	3H	6.4	6.9	6.7	7.1	7.4	5.9	6.4	6.2	6.7	6.9
	4H	0.3	6.8	6.7	7.1	7.4	5.9	6.3	6.2	6.6	6.9
	6H	0.3	6.7	6.6	7.0	7.3	5.8	6.2	6.1	6.5	6.8
	8H	6.2	6.6	6.6	6.9	7.3	5.8	6.1	6.1	6.5	6.8
	12H	6.2	6.6	6.6	6.9	7.3	5.7	6.1	6.1	6.4	6.8
4H	2H	0.3	6.8	6.7	7.1	7.4	5.9	6.3	6.2	6.6	6.9
	3H	6.2	6.6	6.6	6.9	7.3	5.7	6.1	6.1	6.4	6.8
	4H	6.1	6.5	6.5	6.8	7.2	5.6	6.0	6.0	6.3	6.7
	6H	6.0	6.3	6.5	6.7	7.1	5.6	5.9	6.0	6.2	6.7
	8H	6.0	6.3	6.4	6.7	7.1	5.5	5.8	6.0	6.2	6.6
	12H	5.9	6.2	6.4	6.6	7.1	5.5	5.7	5.9	6.1	6.6
8H	4H	6.0	6.3	6.4	6.7	7.1	5.5	5.8	6.0	6.2	6.6
	6H	5.9	6.1	6.4	6.6	7.0	5.4	5.6	5.9	6.1	6.6
	8H	5.8	6.0	6.3	6.5	7.0	5.4	5.6	5.8	6.0	6.5
	12H	5.8	5.9	6.3	6.4	7.0	5.3	5.5	5.8	6.0	6.5
12H	4H	5.9	6.2	6.4	6.6	7.1	5.5	5.7	5.9	6.1	6.6
	6H	5.8	6.0	6.3	6.5	7.0	5.4	5.6	5.8	6.0	6.5
	8H	5.8	5.9	6.3	6.4	7.0	5.3	5.5	5.8	6.0	6.5
Variations with the observer position at spacing:											
S =	1.0H	6.9 / -11.0					6.9 / -11.3				
	1.5H	9.7 / -12.9					9.7 / -13.2				
	2.0H	11.7 / -14.7					11.7 / -15.2				