

Constant current power supply unit IGBT + TRIAC IP20 15W - VIN = 220-240VAC 50/60Hz Ø17

Design iGuzzini

iGuzzini

Last information update: July 2024



Accessory code

MY06: Constant current power supply unit IGBT + TRIAC IP20 15W - VIN = 220-240VAC 50/60Hz Ø17

Technical description

Electronic ballast dimmable TRIAC (Leading Edge) + IGBT (trailing edge) - 500 mA constant current operation. Protection devices: shortcircuits - overloads.

Installation

remote installation.

Colour

Indeterminate (00)

Weight (Kg)

0.09

Dimension (mm) (*)

102x51x29

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Wiring

500 mA for Ø17 Laser recessed luminaires - min 5 - max 10 used. Cables secured with screw terminals.

Complies with EN60598-1 and pertinent regulations



Technical data

Frequency [Hz]:	50/60
Current out [mA]:	500
Inrush current:	1.7 A / 40 µs

Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 50 power supply units B16A: 80 power supply units C10A: 83 power supply units C16A: 136 power supply units
--	---

Minimum dimming %: 5

Overvoltage protection: 2kV Common mode & 1kV Differential mode