

Project name: _____

Type: _____



General information

Luminaire characteristics:

Power input: 6.4W

Lumens: 191 to 220lm (delivered)

Luminaire efficacy: 29 to 39lm/W

Source: White LED, 3000K: 80CRI and 4000K: 75CRI.

Lumen maintenance: >80% of initial lumens at 50 000 hours (L80) LM-80 (LED) / LM-79 tested.

Optics: 360° symmetrical optic with a super-pure aluminum reflector.

Body: Die cast aluminum cylindrical body and stainless steel rods fixed to the base

Electrical: High efficiency electronic power supply, rated 50 000 H. 120V or 277V.

Mounting: Ground anchored.


Finish: Gray (RAL9007)

Weight: 6.94lbs (3.15kg.)


Warranty: 5 years limited warranty.

Certification: cULus listed.

Ratings: IP66, IK10.



TOP VIEW



SIDE VIEW

ORDERING INFO

MODEL	VOLTAGE	FINISH	ACCESSORIES (TO BE ORDERED SEPARATELY)	
<input type="radio"/> I.BG19 - 4000K <input type="radio"/> I.BG20 - 3000K	<input type="radio"/> 120 - 120V <input type="radio"/> 277 - 277V	<input type="radio"/> 15 - Gray	<input type="radio"/> I.B514 - Fixing plate with anchor bolts Ø9½" (240mm) x h: 6⅝" (163mm)	
			<input type="radio"/> I.B504-02 - Black screen for asymmetrical 180° emission	
			<input type="radio"/> I.B506-02 - Black screen for 90° + 90° emission	
			<input type="radio"/> I.B508-02 - Black screen for 180° emission + light blade	

DUE TO CONTINUOUS IMPROVEMENTS, THE INFORMATION HEREIN MAY BE CHANGED WITHOUT NOTICE.

LAST UPDATE: APRIL 28, 2015

MGD - R3