

**Constant current power supply unit DALI/Step-Dim/Middle of the night profile IP20 40W - VIN = 120-277VAC 50/60Hz dimensions: 123x79x33**

Design iGuzzini

iGuzzini

Last information update: October 2023



**Accessory code**

X210: Constant current power supply unit DALI/Step-Dim/Middle of the night profile IP20 40W - VIN = 120-277VAC 50/60Hz dimensions: 123x79x33

**Technical description**

DALI 40W dimmable electronic ballast, with STEP-DIM, ASTRO-DIM and MIDNIGHT PROFILE functions, Vin=120÷277Vac, 50÷60Hz Vout=18÷56Vdc, Iout=350mA (SELV) IP20 protection rating.

| Colour             | Weight (Kg) | Dimension (mm) (*) |
|--------------------|-------------|--------------------|
| Indeterminate (00) | 0.26        | 123x79x33          |

\* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

**Wiring**

Make the connections on the appropriate terminal blocks

**Notes**

Overvoltage protection: 8kV Common Mode, 6kV Differential Mode

Complies with EN60598-1 and pertinent regulations



IP20



**Technical data**

|                   |               |
|-------------------|---------------|
| Frequency [Hz]:   | 50/60         |
| Current out [mA]: | 350           |
| Inrush current:   | 31 A / 186 µs |

|  |  |
|--|--|
| Maximum number of LED power supply units of this type per miniature circuit breaker: | B10A: 18 power supply units<br>B16A: 30 power supply units<br>C10A: 31 power supply units<br>C16A: 51 power supply units |
|--|--|

|                         |  |
|-------------------------|--|
| Minimum dimming %:      | 10                                       |
| Overvoltage protection: | 10kV Common mode & 6kV Differential mode |