
Linealuce

Design Jean-Michel iGuzzini Wilmotte

Last information update: October 2024

Product configuration: UB82

UB82: 47 Recessed Integral - Neutral White - 220-240Vac DALI - L=610mm - Wide Flood optic - Non-slip glass cover



Product code

UB82: 47 Recessed Integral - Neutral White - 220-240Vac DALI - L=610mm - Wide Flood optic - Non-slip glass cover

Technical description

Direct light luminaire, designed to use monochrome LED lamps, DALI 220÷240Vac dimmable with searching and addressing function and non-slip glass cover. Ground-, wall- and ceiling-recessed. Option of installation in continuous lines of up to a max length of 10.5m only for ground-recessed installation. Made up of a body, end caps, an outer casing and caps to be ordered separately. Extruded aluminium body, with die-cast aluminium end caps complete with silicone seals. The painting process includes a multi-step, pretreatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nanostructured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. Lower PPS (polyphenylene sulfide) box for control gear. The top of the optical assembly is closed by an 8 mm thick, non-slip glass screen (conforming to class R13 in accordance with DIN 51130), fixed with silicone. Complete with monochrome multi-LED plate and a 220-240Vac DALI electronic driver (ballast included). Fitted with optics with a plastic (methacrylate) lens. At the bottom of the optical assembly there is a PPS (polyphenylene sulfide) box fitted with two nickel-plated brass cable glands PG11 for pass-through wiring, suitable for cables Ø8.5÷12.5 mm. To fix the optical assembly to the outer casing or false ceiling the product has a quick coupling system using an Allen key. All external screws used are made of A2 stainless steel.



Installation

Ground- and wall-recessed using the outer casing, to be ordered separately, together with the end caps for the optical assembly and outer casing caps. Option of installation in continuous lines of up to a max length of 10.5m only for ground-recessed installation: in this case, too, the joints for the outer casings must be ordered separately. For ground installation a drainage channel must be created or gravel inserted for drainage under the outer casing before installation, to guarantee the degree of protection stated. For ceiling-mounting with plasterboard panels (1-30 mm thick), make the preparation openings as indicated in the instructions sheet and use the steel cables with reinforcement plates in the accessory kit.

Colour	Weight (Kg)
White (01) Black (04) Grey (15) Rust Brown (F5)	2.75

Mounting

wall recessed|Floor recessed|ceiling recessed|ground recessed

Wiring

Complete with DALI control card and a 220÷240Vac electronic ballast. For the electrical connection the product has a lower box holding the terminal board (5+5poles, max 2.5mm²) and two nickel-plated brass cable glands PG11 for pass-through wiring, suitable for cables Ø8.5÷12.5 mm.

Notes

Product complete with LED lamp.



Technical data					
Im system:	936	MacAdam Step:	3		
W system:	22.7	Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)		
Im source:	2400	Life Time LED 2:	100,000h - L80 - B10 (Ta 40°C)		
W source:	17	Voltage [Vin]:	230		
Luminous efficiency (lm/W,	41.2	Lamp code:	LED		
real value):	Number of lamps for		al 1		
Im in emergency mode:	-	assembly:			
Total light flux at or above	936	ZVEI Code:	LED		
an angle of 90° [Lm]:		Number of optical	1		
Light Output Ratio (L.O.R.)	39	assemblies:			
[%]:		Intervallo temperatura	from -30°C to 50°C.		
Beam angle [°]:	48°	ambiente:			
CRI (minimum):	80	Control:	DALI-2		
Colour temperature [K]:	4000				

Polar

lmax=845 cd	C25-205 γ=179°	Lux				
	180°	h	d1	d2	Em	Emax
/	+7/	2	1.8	1.8	157	211
		4	3.6	3.6	39	53
90°	90°	6	5.4	5.3	17	23
600 α=48°	46.	8	7.2	7.1	10	13