

DALI constant current power supply IP68 30W with 3 outgoing cables L = 400 - Vin = 220 ÷ 240Vac 50 / 60Hz Iout = 700mA

Design iGuzzini

iGuzzini

Last information update: September 2023

Accessory code

PB27: DALI constant current power supply IP68 30W with 3 outgoing cables L = 400 - Vin = 220 ÷ 240Vac 50 / 60Hz Iout = 700mA

Technical description


30W electronic power supply - DALI dimmable - IP68 with 3 outlet cables.

VIN = 220 ÷ 240Vac 50 / 60Hz, Iout = 700mA.

Dimensions: 121.5x53.5x26mm.

Adjustment 1±100%. Designed to work with DALI-2 systems.

Protected against short circuits, mains overvoltages and overloads.



Colour

Indeterminate (00)

Dimension (mm) (*)

122x54x26

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Wiring

Outlet cables L= 400 mm:

1x Mains input

1x DALI control

1x Outlet to devices

Notes

Compatible with DALI and DALI-2 systems.

Complies with EN60598-1 and pertinent regulations



Technical data

Frequency [Hz]:	50/60	Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 31 power supply units B16A: 50 power supply units C10A: 52 power supply units C16A: 85 power supply units
Current out [mA]:	700		
Inrush current:	5 A / 50 µs		
		Minimum dimming %:	1
		Overvoltage protection:	4kV Common mode & 4kV Differential mode