

**DALI constant current power supply IP68 30W with 3 outgoing cables L = 400 - Vin = 220 ÷ 240Vac 50 / 60Hz Iout = 700mA**

Design iGuzzini

iGuzzini

Last information update: July 2024

**Accessory code**

PB27: DALI constant current power supply IP68 30W with 3 outgoing cables L = 400 - Vin = 220 ÷ 240Vac 50 / 60Hz Iout = 700mA

**Technical description**


30W electronic power supply - DALI dimmable - IP68 with 3 outlet cables.

VIN = 220 ÷ 240Vac 50 / 60Hz, Iout = 700mA.

Dimensions: 121.5x53.5x26mm.

Adjustment 1÷100%. Designed to work with DALI-2 systems.

Protected against short circuits, mains overvoltages and overloads.



**Colour**

Indeterminate (00)

**Dimension (mm) (\*)**

122x54x26

\* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

**Wiring**

Outlet cables L= 400 mm:

1x Mains input

1x DALI control

1x Outlet to devices

**Notes**

Compatible with DALI and DALI-2 systems.

Complies with EN60598-1 and pertinent regulations



**Technical data**

Frequency [Hz]: 50/60

Current out [mA]: 700

Inrush current: 5 A / 50 µs

Maximum number of LED

power supply units of this

type per miniature circuit

breaker:

B10A: 31 power supply units

B16A: 50 power supply units

C10A: 52 power supply units

C16A: 85 power supply units

Minimum dimming %:

1

Overvoltage protection:

4kV Common mode & 4kV

Differential mode