

Palco Recessed / Surface


Design Artec
Studio

iGuzzini

Last information update: October 2024

Product configuration: QC12

QC12: Palco single recess $\varnothing 19$ - medium - remote driver



Product code

QC12: Palco single recess $\varnothing 19$ - medium - remote driver

Technical description

Miniaturised adjustable spotlight for recessed installation. Spotlight body with a cast zamak dissipation system and rotation units - machined aluminium recess base - steel wire fixing springs. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90° . The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.

Installation

Recessed base with surface stop plate - steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole $\varnothing 19$ mm.

Colour

White (01) | Black (04)

Weight (Kg)

0.06


Mounting

wall recessed|ceiling recessed

Wiring

Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	127	CRI (minimum):	90
W system:	2	Colour temperature [K]:	3000
Im source:	190	MacAdam Step:	2
W source:	2	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	63.7	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	67	Number of optical assemblies:	1
Beam angle [$^\circ$]:	24 $^\circ$	LED current [mA]:	700

Polar

Imax=660 cd	Lux			
	h	d	Em	Emax
	1	0.4	542	660
	2	0.9	135	165
	3	1.3	60	73
	4	1.7	34	41