

Last information update: May 2024

Product configuration: MC10

MC10: Square recessed luminaire - 226x226 mm H=103 mm - LED warm white - DALI ballast, general light optic

**Product code**MC10: Square recessed luminaire - 226x226 mm H=103 mm - LED warm white - DALI ballast, general light optic **Attention! Code no longer in production****Technical description**

Recessed fixed square luminaire designed to use a LED lamp. Version with rim for surface-mounting. Multi-faceted reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Die-cast aluminium body and passive dissipation system. Product complete with 2000 lm DALI LED unit in a warm white tone 3000K and electronic driver separate from the luminaire. General light distribution.

Installation

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 25 mm.

Colour

White / Aluminium (39)

Weight (Kg)

1.95

Mounting

ceiling recessed

Wiring

Product complete with DALI electronic components

Complies with EN60598-1 and pertinent regulations




On the visible part of the product once installed

pending

Technical data


lm system:	1920	Colour temperature [K]:	3000
W system:	21	MacAdam Step:	3
lm source:	2000	Life Time LED 1:	50,000h - L80 - B10 (Ta 25°C)
W source:	18	Lamp code:	LED
Luminous efficiency (lm/W, real value):	91.4	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	96	Control:	DALI
CRI:	80		

Polar

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	68	59	52	48	57	52	51	45	47
1.0	75	66	60	56	65	60	59	53	56
1.5	85	78	73	69	77	72	71	66	69
2.0	90	85	81	78	83	80	79	74	77
2.5	93	89	86	83	87	84	83	79	82
3.0	95	92	89	86	90	87	86	82	85
4.0	97	94	92	90	92	90	89	85	89
5.0	98	96	94	92	94	92	91	87	91

Luminance curve limit



UGR diagram

Corrected UGR values (at 2000 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	22.4	23.4	22.7	23.7	23.9	22.5	23.4	22.8	23.7	23.9
	3H	22.3	23.2	22.7	23.5	23.8	22.9	23.7	23.2	24.0	24.3
	4H	22.3	23.0	22.6	23.3	23.7	22.9	23.7	23.2	24.0	24.3
	6H	22.2	22.9	22.5	23.2	23.5	22.8	23.5	23.2	23.8	24.2
	8H	22.1	22.8	22.5	23.2	23.5	22.8	23.5	23.1	23.8	24.1
	12H	22.1	22.8	22.5	23.1	23.5	22.7	23.4	23.1	23.7	24.1
4H	2H	22.8	23.6	23.2	23.9	24.2	22.3	23.1	22.6	23.4	23.7
	3H	22.8	23.4	23.1	23.8	24.1	22.7	23.3	23.1	23.7	24.0
	4H	22.7	23.2	23.1	23.6	24.0	22.7	23.3	23.1	23.6	24.0
	6H	22.6	23.1	23.0	23.5	23.9	22.6	23.1	23.0	23.5	23.9
	8H	22.5	23.0	23.0	23.4	23.9	22.6	23.0	23.0	23.4	23.9
	12H	22.5	22.9	23.0	23.3	23.8	22.5	22.9	23.0	23.4	23.8
8H	4H	22.5	23.0	23.0	23.4	23.9	22.6	23.0	23.0	23.4	23.9
	6H	22.5	22.8	22.9	23.3	23.8	22.5	22.9	23.0	23.3	23.8
	8H	22.4	22.7	22.9	23.2	23.7	22.4	22.8	22.9	23.2	23.7
	12H	22.4	22.6	22.9	23.1	23.6	22.4	22.7	22.9	23.2	23.7
12H	4H	22.5	22.9	23.0	23.3	23.8	22.5	22.9	23.0	23.4	23.8
	6H	22.4	22.7	22.9	23.2	23.7	22.4	22.8	22.9	23.2	23.7
	8H	22.4	22.6	22.9	23.1	23.6	22.4	22.7	22.9	23.2	23.7
Variations with the observer position at spacing:											
S =		0.5 / -0.5					0.5 / -0.5				
		1.5 / -4.1					1.5 / -3.8				
		2.3 / -17.2					2.3 / -16.6				