Design iGuzzini

iGuzzini

Last information update: March 2025





Product code

156B: Linear module LB XS for 48V Superrail track - BLE Casambi - LGC Wall Washer 5 cells

Technical description

Linear recessed miniaturised luminaire for LED lamps, specialised for vertical wall lighting and complete with adapter for installation on a Superrail LV track. The adapter made of a thermoplastic material includes the DC/DC driver circuit and Bluetooth protocol. Integrated «Bluetooth Casambi» technology allows each light module inserted on the track to be adjusted independently. Bluetooth Low Energy (Casambi) technology. Frequency 2.4 GHz BLE. The luminaire can be controlled with the Casambi App that enables on off, dimming and scene recall functions. The app is available on the Apple Store and Google Play Store. It can be integrated in the system's "Mesh" network that allows multiple luminaires to be controlled. OTA (over the air) update via app. Integrated Beacon that can be activated via Smart Light Control (iBeacon) that enables functions including push notification and indoor navigation-wayfinding. The patented optic system guarantees a homogeneous and effective emission on the wall, as well as avoiding shadow zones near the ceiling. The black polycarbonate perimeter frame is designed to significantly reduce the effect of longitudinal glare while also guaranteeing maximum light uniformity on the wall. Flux enhancer - superpure aluminium reflector - asymmetrical textured PMMA screen. Main body made of extruded aluminium. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

Installation

An adapter is used to fix the device mechanically and tool-free to the 48V track. Max luminaire-luminaire distance (*): 8 m; max smartphone-luminaire distance (*): 20 m.

Colour

Black / Black (43) | Black / White (47)

Mounting

Low voltage track

Wiring

Direct connection on 48V track. Track power supply unit to be ordered separately. Luminaire that can be controlled with Bluetooth technology (Casambi).

Motor

(*) The maximum distance for Bluetooth installations is affected by physical obstacles, like walls, metal panels and the layout of the system. We suggest that a test is conducted at the installation site. Technical and anti-glare accessories available; with option of the combined installation of two internal accessories.

Complies with EN60598-1 and pertinent regulations





On the visible part of the product once installed





Technical data			
Im system:	264 (*)	CRI:	90
W system:	15 (*)	Colour temperature [K]:	3500
Im source:	850 (*)	Number of lamps for optical	1
W source:	10 (*)	assembly:	
Luminous efficiency (lm/W,	17.0 (*)	ZVEI Code:	LED
real value):		Number of optical	1
Im in emergency mode:	-	assemblies:	
Light Output Ratio (L.O.R.) [%]:	31 (*)	Control:	Casambi