

Berlin

design Piano Design Workshop



- Pendant installation.
- Die-cast aluminium control gear box.
- Die-cast aluminium anchoring base equipped with power cable and hooking device, plus millimetre-accurate adjustment of the steel cable.
- Screen with transparent safety glass housed in a die-cast aluminium ring with a seal.
- Adjustment of light beam opening.

Lighting distribution

Down light


Version with aluminium reflector for down light.




Up/down light

Version with reflector made of glass + aluminium for down/up light.







W	optic	code colour
Optical assembly with aluminium reflector		
TC-TEL (GX24q-4)		
Electronic		
42W	106°	4302 78
Optical assembly with aluminium reflector		
HIT (G12) - HIT-CE (G12)		
Electromagnetic		
70W	GL	4305 78
150W	GL	4306 78
Complete with safety glass		



W	optic	code colour
Optical assembly with aluminum/glass reflector		
TC-TEL (GX24q-4)		
Electronic		
42W	GL	4334 78
Optical assembly with aluminum/glass reflector		
HIT (G12) - HIT-CE (G12)		
Electromagnetic		
70W	GL	4337 78
70W (HIT-CE)		
150W	GL	4338 78
150W (HIT-CE)		
Complete with safety glass		








W	optic	code colour
Optical assembly with aluminium reflector		
HIE (E40)		
Electromagnetic		
250W	96°	4327 78
Complete with safety glass		



W	code colour
Optical assembly with aluminum/glass reflector	
HIE (E40)	
Electromagnetic	
250W	4343 78
Complete with safety glass	

accessories



	code	colour	code	colour
 Class II suspension and connection kit L=2000	4449	15	4449	15
 Class II suspension and connection kit L=2000	4447	15	4447	15
 Safety glass complete with seal Use of this accessory guarantees the product IP65 protection	4442	15	---	---
 Anti-glare screen Using this accessory helps increase visual comfort but also causes a reduction in yield	4450	04 for 4305-4306-4337-4338	4455	04 for 4343
	---	---	4456	04 for 4327