iGuzzini

Last information update: February 2025

# Product configuration: Q591

Q591: Frame 5 LED section - Wall Washer

Q591: Frame 5 LED section - Wall Washer

## Technical description

Product code

Miniaturized recessed linear luminaire for LED lamps. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient and homogeneous effect on walls from top to bottom and avoids shadow zones near the ceiling. Main body with die-cast zamak radiant surface, version with perimeter surface frame. Flux enhancer - superpure aluminium reflector - asymmetrical textured PMMA screen - black polycarbonate internal perimeter frame. Supplied with a power supply unit connected to the luminaire.

## Installation

\* Colours on request

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 24 x 96.

#### Colour

Mounting

Wiring

ceiling recessed


Black / Black (43) | Black / White (47) | Grey / Black (74)\*

Weight (Kg) 0.35





On the power supply unit with terminal board included.



Technical data			
Im system:	346	Colour temperature [K]:	3000
W system:	12.4	MacAdam Step:	2
Im source:	910	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
W source:	9.9	Voltage [Vin]:	230
Luminous efficiency (Im/W,	27.9	Lamp code:	LED
real value):		Number of lamps for optical	1
Im in emergency mode:	-	assembly:	
Total light flux at or above an angle of 90° [Lm]:		ZVEI Code:	LED
		Number of optical	1
Light Output Ratio (L.O.R.)	38	assemblies:	
[%]:		Control:	DALI-2
CRI (minimum):	90		

