


Last information update: May 2024

**Product configuration: QB36**

QB36: Angular LED module - Minimal Down HO - ON-OFF - General Light - Neutral



**Product code**

QB36: Angular LED module - Minimal Down HO - ON-OFF - General Light - Neutral **Attention! Code no longer in production**

**Technical description**

Angular element for Minimal (frameless) flush with ceiling version profiles; including a Neutral 4000K LED module High Output version. The module optic and structural fittings allow high luminous flux and system efficiency values. Methacrylate opal screen for diffused general light; screen set up for overlap connections. Integrated control gear. Pass-through wiring for continuous lines:

**Installation**

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately.

**Colour**

White (01) | Black (04) | Aluminium (12)

**Weight (Kg)**

4.17

**Mounting**

ceiling recessed|ceiling surface|ceiling pendant

**Wiring**

The angular profile is supplied with pass-through wiring for continuous lines. Quick coupling terminal blocks to simplify connections between the luminaires. LED module complete with integrated ON-OFF non-dimmable control gear.

**Notes**

Important: the Minimal angular module is only available for Down emission. Take care when configuring the system; to complete a continuous line with an angular profile correctly, two initial modules are required, one for each end of the corner.

Complies with EN60598-1 and pertinent regulations



**Technical data**

Im system:	3116	CRI:	80
W system:	24.6	Colour temperature [K]:	4000
Im source:	2050	MacAdam Step:	3
W source:	11	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	126.7	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	2

**Polar**

