


Last information update: May 2024

Product configuration: P658

P658: spotlight - neutral white - spot optic

**Product code**P658: spotlight - neutral white - spot optic **Attention! Code no longer in production****Technical description**

Adjustable spotlight with adapter for installation on DALI track. Neutral White (4000K) LED source with COB technology. DALI dimmable control gear housed inside the track-mounted power supply box. The luminaire is made of die-cast aluminium and thermoplastic. OPTI BEAM superpure aluminium reflector with high luminous efficacy and uniform distribution, spot optic. Features 90° inclination on the horizontal plane and 360° rotation around the vertical axis, with mechanical locking device for aiming. Passive cooling system. Possibility of installing a refractor, to be ordered separately, for elliptical light beam distribution.

Installation

The luminaire can be installed on a standard track, false ceilings or on an appropriate channel incorporating an electrified track.

Colour

White (01) | Black (04)

Weight (Kg)

0.68

Mounting

three circuit track|ceiling surface

Wiring

product inclusive of DALI dimmable components incorporated into the track-mounted box.

Complies with EN60598-1 and pertinent regulations



IP20

IP40

for optical
assembly**Technical data**

lm system:	1104	CRI:	80
W system:	12.4	Colour temperature [K]:	4000
lm source:	1600	MacAdam Step:	2
W source:	11	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	89	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	69	Number of optical assemblies:	1
Beam angle [°]:	16°	Control:	DALI

Polar

Imax=6986 cd		Lux			
		h	d	Em	Emax
	90°	2	0.6	1377	1747
		4	1.1	344	437
		6	1.7	153	194
	0°	8	2.2	86	109
$\alpha = 16^\circ$					