

Palco Recessed / Surface

Design Artec
Studio

iGuzzini

Last information update: February 2025

Product configuration: QX23

QX23: Palco single surface Ø19 - medium - remote driver

Product code

QX23: Palco single surface Ø19 - medium - remote driver

Technical description

Miniaturised adjustable spotlight for surface installation. Spotlight body with a cast zamak dissipation system and rotation unit - shaped steel fixing plate - thermoplastic surface cover base with stainless steel locking mechanism. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.

Installation

Installation surface plate fastening - spotlight unit attached to cover base with a locking mechanism.

Colour

White (01) | Black (04)

Weight (Kg)

0.06


Mounting

wall surface|ceiling surface

Wiring

Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	154	CRI (minimum):	90
W system:	2	Colour temperature [K]:	4000
Im source:	230	MacAdam Step:	2
W source:	2	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	77.1	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	67	Number of optical assemblies:	1
Beam angle [°]:	24°	LED current [mA]:	700

Polar

Imax=799 cd	Lux			
	h	d	Em	E _{max}
	1	0.4	656	799
	2	0.9	164	200
	3	1.3	73	89
	4	1.7	41	50