


Last information update: October 2024



**Product code**

2552: Recessed frame - LED - Neutral white - Integrated Electronic control gear - Wall washer optic

**Technical description**

Miniaturized recessed rectangular luminaire with LEDs. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Asymmetrical optic system designed to achieve an effective wall washer distribution. Flux enhancer - superpure aluminium reflector - screen in PMMA with ribbed texture; a special film in acrylic material, combined with the screen, allow for a uniform and effective light emission on the wall. Black polycarbonate internal perimeter frame. Supplied with electronic control gear connected to the luminaire. Warm white LED.

**Installation**

recessed with steel springs for false ceilings from 1 to 25 mm; can be installed on ceilings and walls (vertical + horizontal) - preparation slot 37 x 141. To light the wall correctly check the installation distances and centre-to-centre distances on the instructions sheet.

**Colour**

Black / Black (43) | Black / White (47)

**Mounting**

wall recessed|ceiling recessed


**Wiring**

on power box: screw connections

**Notes**

accessory anti-glare screen available code MPX7

Complies with EN60598-1 and pertinent regulations



**Technical data**

lm system:	445 (*)	Beam angle [°]:	50° / 63° (*)
W system:	10 (*)	CRI:	90
lm source:	1112 (*)	Colour temperature [K]:	3500
W source:	10 (*)	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	44.0 (*)	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1