


Last information update: May 2024

Product configuration: BX33

BX33: Outdoor ceiling-mounted luminaire - Warm White COB Led - integrated dimm. ballast DALI - 30° Flood Optic

**Product code**BX33: Outdoor ceiling-mounted luminaire - Warm White COB Led - integrated dimm. ballast DALI - 30° Flood Optic **Attention! Code no longer in production****Technical description**

Ceiling-mounted luminaire designed to use Warm White COB LED lamps with a Flood optic. The luminaire consists of an optical assembly/component-holding box and base for ceiling-mounting. The optical assembly, front frame, rear door and ceiling-mount base are made of die-cast aluminium alloy painted with a smooth finish (grey RAL 9007) or a textured finish (white RAL 9016). The painting process includes a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The next painting stage consists of a primer and a liquid acrylic paint, cured at 150°, with a high level of weather and UV ray resistance. The tempered sodium-calcium glass cover has customised serigraphy, is 4mm thick, and joined to the frame with silicone. The frame is fastened to the optical assembly by two M5 AISI 304 stainless steel captive screws and a steel safety cable. The product comes complete with a neutral white colour, monochrome COB LED circuit, an optic with a 99.93% pure aluminium OPTIBEAM reflector with a polished, anodized surface and built-in electronic ballast. The component-holding box, in the rear of the luminaire, is set up to hold the control gear, which is fixed with captive screws on a galvanised steel pull-out plate. The control gear can be accessed via the ceiling-mounting base with quick-connecting system and the rear door made of painted aluminium alloy, fixed to the product body with four M5 AISI 304 stainless steel captive screws. A galvanised steel safety cable secures the upper base to the product. The internal silicone seals guarantee watertightness IP66h Set up for pass-through wiring using PG13.5 polyamide cable glands, designed for cables with diameters between 8.5÷12.5 mm. The connection to the mains is made using a 3-pole terminal block with a quick-coupling system. Cables with quick-coupling terminals connect the terminal block and the control gear. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN60598-1 standards and particular requirements.

Installation

Ceiling-mounted using the special base. Secure using screw anchors for concrete, cement and solid brick.

Colour

White (01) | Grey (15)

Weight (Kg)

6.5

Mounting

ceiling surface|free standing

Wiring

Control gear complete with DALI dimmable electronic ballast (120÷240V ac 50/60Hz) and quick-coupling terminals.

Notes


Dimming function with pushbutton (DIM PUSH): for this operation consult the instructions included in the package.

Complies with EN60598-1 and pertinent regulations


**Technical data**

Im system:	4310	Colour temperature [K]:	3000
W system:	41.6	MacAdam Step:	2
Im source:	5400	Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)
W source:	35	Life Time LED 2:	100,000h - L80 - B10 (Ta 40°C)
Luminous efficiency (Im/W, real value):	103.6	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	80	Number of optical assemblies:	1
Beam angle [°]:	32°	Intervallo temperatura ambiente:	from -20°C to +35°C.
CRI (minimum):	80	Control:	DALI

Polar



Isolux



UGR diagram

Corrected UGR values (at 5 400 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling	cav	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	1.8	3.9	2.2	4.2	4.6	1.8	3.9	2.2	4.2	4.6
	3H	1.7	3.4	2.0	3.7	4.0	1.6	3.3	2.0	3.7	4.0
	4H	1.6	3.0	2.0	3.4	3.7	1.6	3.0	2.0	3.4	3.7
	6H	1.6	2.7	2.0	3.0	3.4	1.5	2.7	1.9	3.0	3.4
	8H	1.5	2.6	1.9	3.0	3.4	1.5	2.6	1.9	3.0	3.3
	12H	1.5	2.6	1.9	2.9	3.3	1.5	2.5	1.9	2.9	3.3
4H	2H	1.6	3.0	2.0	3.4	3.7	1.6	3.0	2.0	3.4	3.7
	3H	1.5	2.6	1.9	2.9	3.3	1.5	2.6	1.9	2.9	3.3
	4H	1.4	2.4	1.9	2.8	3.2	1.4	2.4	1.9	2.8	3.2
	6H	1.1	2.7	1.6	3.2	3.7	1.1	2.7	1.5	3.2	3.6
	8H	1.0	2.8	1.4	3.3	3.8	0.9	2.8	1.4	3.3	3.8
	12H	0.8	2.8	1.3	3.3	3.8	0.8	2.8	1.3	3.3	3.8
8H	4H	0.9	2.8	1.4	3.3	3.8	1.0	2.8	1.4	3.3	3.8
	6H	0.8	2.7	1.3	3.1	3.7	0.8	2.7	1.3	3.2	3.7
	8H	0.8	2.5	1.3	3.0	3.5	0.8	2.5	1.3	3.0	3.5
	12H	1.0	2.1	1.5	2.6	3.1	1.0	2.1	1.5	2.6	3.1
12H	4H	0.8	2.8	1.3	3.3	3.8	0.8	2.8	1.3	3.3	3.8
	6H	0.8	2.5	1.3	3.0	3.5	0.8	2.5	1.3	3.0	3.5
	8H	1.0	2.1	1.5	2.6	3.1	1.0	2.1	1.5	2.6	3.1
Variations with the observer position at spacing:											
S =		1.0H	0.6 / -8.4				0.6 / -8.4				
		1.5H	9.4 / -9.5				9.4 / -9.5				
		2.0H	11.4 / -10.4				11.4 / -10.4				