

Last information update: February 2025

Product configuration: RG32

RG32: Pendant Tecnica Evo - Ø117 body - DALI

**Product code**


RG32: Pendant Tecnica Evo - Ø117 body - DALI

Technical description

Pendant luminaire fitted with an adapter for installation on an electrified DALI track. High yield LED lamp. Die-cast aluminium luminaire. Optical system with high performance P.V.D. (Physical Vapour Deposition) anti-scratch aluminium reflector that offers an excellent light efficiency ratio. Balanced pendant system with double steel cable and adjustment system. Fitted with mechanical aiming locks, so rotation and tilting movements can be locked in position to ensure efficient light aiming even after the original installation or during maintenance. Integrated DALI dimmable power supply unit. Designed to house other optical accessories in the range. Interchangeable reflectors are available, which allow the emission angle to be varied as required, even after the original installation.

Installation

Installation on an electrified track.



Colour	Weight (Kg)
White (01) Black (04)	1.53

Mounting

dali track


Wiring

Built-in DALI dimmable power supply.

Complies with EN60598-1 and pertinent regulations

**Technical data**


Im system:	5035	CRI (minimum):	80
W system:	38.2	Colour temperature [K]:	3000
Im source:	5300	MacAdam Step:	2
W source:	34	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	131.8	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	95	Number of optical assemblies:	1
Beam angle [°]:	52°	Control:	DALI-2

Polar

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	85	80	76	74	79	76	76	72	76
1.0	88	84	81	79	83	81	80	77	81
1.5	93	90	88	86	89	87	86	83	87
2.0	96	94	92	91	93	91	90	87	92
2.5	98	96	95	94	95	94	93	90	95
3.0	99	98	97	96	97	96	94	92	97
4.0	101	100	99	98	98	97	96	94	99
5.0	101	101	100	100	99	98	97	95	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 5300 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceil/cav	walls	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50		
walls	work pl.	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.30		
work pl.	Room dim	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20		
X	Y	viewed crosswise					viewed endwise				
2H	2H	20.1	20.7	20.4	20.9	21.2	20.1	20.7	20.4	20.9	21.2
3H	2H	20.0	20.5	20.3	20.8	21.0	20.0	20.5	20.3	20.8	21.0
4H	2H	19.9	20.4	20.2	20.7	21.0	19.9	20.4	20.2	20.7	21.0
6H	2H	19.8	20.3	20.2	20.6	20.9	19.8	20.3	20.2	20.6	20.9
8H	2H	19.8	20.2	20.1	20.6	20.9	19.8	20.2	20.1	20.5	20.9
12H	2H	19.7	20.2	20.1	20.5	20.9	19.7	20.2	20.1	20.5	20.9
4H	4H	19.9	20.4	20.2	20.7	21.0	19.9	20.4	20.2	20.7	21.0
3H	4H	19.8	20.2	20.1	20.5	20.9	19.8	20.2	20.1	20.5	20.9
4H	4H	19.7	20.0	20.1	20.4	20.8	19.7	20.0	20.1	20.4	20.8
6H	4H	19.6	19.9	20.0	20.3	20.7	19.6	19.9	20.0	20.3	20.7
8H	4H	19.5	19.8	20.0	20.3	20.7	19.5	19.8	20.0	20.3	20.7
12H	4H	19.5	19.8	19.9	20.2	20.6	19.5	19.8	19.9	20.2	20.6
8H	8H	19.5	19.8	20.0	20.3	20.7	19.5	19.8	20.0	20.3	20.7
6H	8H	19.4	19.7	19.9	20.1	20.6	19.4	19.7	19.9	20.1	20.6
8H	8H	19.4	19.6	19.9	20.1	20.6	19.4	19.6	19.9	20.1	20.6
12H	8H	19.3	19.5	19.8	20.0	20.5	19.3	19.5	19.8	20.0	20.5
12H	4H	19.5	19.8	19.9	20.2	20.6	19.5	19.8	19.9	20.2	20.6
6H	4H	19.4	19.6	19.9	20.1	20.6	19.4	19.6	19.9	20.1	20.6
8H	4H	19.3	19.5	19.8	20.0	20.5	19.3	19.5	19.8	20.0	20.5
Variations with the observer position at spacing:											
S =	1.0H	5.5	/ -10.6			5.5	/ -10.6				
	1.5H	8.3	/ -13.6			8.3	/ -13.6				
	2.0H	10.3	/ -15.0			10.3	/ -15.0				