
iGuzzini

Last information update: May 2024

Product configuration: 4901+1639

4901: Projector with 75 W QR 111 dimmable electronic transformer





Product code

4901: Projector with 75 W QR 111 dimmable electronic transformer Attention! Code no longer in production

Technical description

Die-cast aluminium and thermoplastic projector. It can be rotated by 340° with respect to the vertical axis and inclined by +/- 100° with respect to the horizontal axis. Mechanical screw-locking devices, graduated scales and adjustable friction devices guarantee the precise positioning of the light beam. The projector is equipped with a die-cast aluminium base for ceiling or wall application. The wiring foresees the use of a dimmable electronic transformer. Various accessories are available, such as adjustable flaps, wall-washer screen, IR filter, refractor for the elliptical distribution of the light flow and coloured filters.

Installation Wall or ceiling

Colour

White (01) | Grey (15)

Mounting

wall surface|ceiling surface

Wiring Complete with electromagnetic transformer for 75W halogen lamps, fitted inside the luminaire.

Notes

The luminaire becomes IP40 with the use of accessory glasses. For the photometric data of the luminaire, refer to the photometric characteristics of the light source.

Complies with EN60598-1 and pertinent regulations



Technical data			
Im system:	796	CRI (minimum):	100
W system:	82	Colour temperature [K]:	3000
Im source:	796	Lamp maximum intensity	1700
W source:	75	[cd]:	
Luminous efficiency (Im/W,	9.7	Voltage [Vin]:	12
real value):		Lamp code:	1639
Im in emergency mode:	-	Socket:	G53
Total light flux at or above an angle of 90° [Lm]:	0	Number of lamps for optical assembly:	1
Light Output Ratio (L.O.R.) [%]:	100	ZVEI Code:	QR 111
		Number of optical	1
Beam angle [°]:	42°	assemblies:	

Polar

