

---

**Constant current power supply unit non dimmable IP20 20W - Vin = 220-240 Vac 50/60 Hz - I out = 250-700mA**

---

Design iGuzzini

iGuzzini

Last information update: October 2023

**Accessory code**

X020: Constant current power supply unit non dimmable IP20 20W - Vin = 220-240 Vac 50/60 Hz - I out = 250-700mA

**Technical description**

Constant current non-dimmable electronic power supply max 20 W. Input Vin=220÷240 Vac 50÷60 Hz.

Constant current output 250÷700 mA selectable with a DIP-SWITCH.

Product features include overvoltage protection, short circuit protection, overcurrent and overtemperature protection.

**Installation**

Positioned on top of or inside electrical boxes. Fitted with slots for fastening with screws, if required.

**Colour**  
Indeterminate (00)**Weight (Kg)**  
0.2**Dimension (mm) (\*)**  
110x52x22

\* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

**Wiring**Input and output terminals on same side (cable cross-section up to 1.5 mm<sup>2</sup>).

Primary and secondary cable clamp for cables with a diameter of min. 3 mm - max. 8 mm.

**Notes**

To set the current and for the minimum and maximum quantities of luminaires that can be connected to this power supply, consult the reference product instruction sheet.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Frequency [Hz]: 0/50/60

Current out [mA]: 250

Inrush current: 5 A / 50 µs

Maximum number of LED power supply units of this type per miniature circuit breaker:

B10A: 31 power supply units  
B16A: 50 power supply units  
C10A: 52 power supply units  
C16A: 85 power supply units

Overvoltage protection:

2kV Common mode &amp; 1kV Differential mode