




Last information update: April 2025

Product configuration: MQ38

MQ38: Adjustable 2 x 15 - cell Recessed frame - LED - Warm white - DALI dimmable power supply - Flood Beam



Product code

MQ38: Adjustable 2 x 15 - cell Recessed frame - LED - Warm white - DALI dimmable power supply - Flood Beam

Technical description

Recessed rectangular luminaire with LEDs. Shaped steel sheet structural compartment with outer rim. The two linear elements with 15 lighting cells, in die-cast aluminium and independently adjustable, can be used to direct the emission with a tilting adjustability of +/- 30°. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare. Supplied with DALI dimmable control gear connected to the luminaire. Warm white LED.

Installation

recessed with mechanical blocking system for false ceilings from 1 to 25 mm; can be installed on ceilings and walls (vertical + horizontal) - preparation slot 135 x 428

Colour

Black / Black (43) | Black / White (47) | Grey / Black (74)*

Weight (Kg)

3.36

* Colours on request

Mounting

wall recessed|ceiling recessed

Wiring

On power box: screw and quick release connections. The product is fitted with a separate control gear for each lighting body; possibility of separate switching

Notes

dimming function with pushbutton (TOUCH DIM/PUSH): for this option consult the instructions included in the package

Complies with EN60598-1 and pertinent regulations



Technical data

| | | | |
|--|------|---------------------------------------|---------------------------------|
| lm system: | 5103 | CRI (typical): | 92 |
| W system: | 67.3 | Colour temperature [K]: | 3000 |
| lm source: | 3150 | MacAdam Step: | 3 |
| W source: | 29 | Life Time LED 1: | > 50,000h - L90 - B10 (Ta 25°C) |
| Luminous efficiency (lm/W, real value): | 75.8 | Lamp code: | LED |
| lm in emergency mode: | - | Number of lamps for optical assembly: | 1 |
| Total light flux at or above an angle of 90° [Lm]: | 0 | ZVEI Code: | LED |
| Light Output Ratio (L.O.R.) [%]: | 81 | Number of optical assemblies: | 2 |
| Beam angle [°]: | 32° | Control: | DALI-2 |
| CRI (minimum): | 90 | | |

Polar

| Imax=8571 cd | CIE nL 0.81 100-100-100-100-81 UGR <10-<10 DIN A.61 UTE 0.81A+0.00T F*1=1000 F*1+F*2=1000 F*1+F*2+F*3=1000 CIBSE LG3 L<1500 cd/m² at 65° UGR<10 L<1500 cd/mq @65° | Lux | | | |
|--------------|--|-----|-----|------|------------------|
| | | h | d | Em | E _{max} |
| | | 2 | 1.1 | 1628 | 2143 |
| | | 4 | 2.3 | 407 | 536 |
| | | 6 | 3.4 | 181 | 238 |
| | | 8 | 4.6 | 102 | 134 |

Utilisation factors

| R | 77 | 75 | 73 | 71 | 55 | 53 | 33 | 00 | DRR |
|------|----|----|----|----|----|----|----|----|-----|
| K0.8 | 73 | 70 | 67 | 65 | 69 | 66 | 66 | 64 | 78 |
| 1.0 | 76 | 73 | 71 | 69 | 72 | 70 | 70 | 67 | 83 |
| 1.5 | 80 | 78 | 76 | 74 | 77 | 75 | 74 | 72 | 89 |
| 2.0 | 83 | 81 | 79 | 78 | 80 | 78 | 78 | 75 | 93 |
| 2.5 | 84 | 83 | 82 | 81 | 82 | 81 | 80 | 78 | 96 |
| 3.0 | 85 | 84 | 83 | 83 | 83 | 82 | 81 | 79 | 98 |
| 4.0 | 86 | 85 | 85 | 84 | 84 | 84 | 82 | 81 | 99 |
| 5.0 | 87 | 86 | 86 | 86 | 85 | 84 | 83 | 81 | 100 |

UGR diagram

| Corrected UGR values (at 3150 lm bare lamp luminous flux) | | | | | | | | | | | |
|---|------|------------------|------|------|------|------|----------------|------|------|------|------|
| Reflect.: | | 0.70 | 0.70 | 0.50 | 0.50 | 0.30 | 0.70 | 0.70 | 0.50 | 0.50 | 0.30 |
| ceiling/cav | | 0.70 | 0.70 | 0.50 | 0.50 | 0.30 | 0.70 | 0.70 | 0.50 | 0.50 | 0.30 |
| walls | | 0.50 | 0.30 | 0.50 | 0.30 | 0.30 | 0.50 | 0.30 | 0.50 | 0.30 | 0.30 |
| work pl. | | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 |
| Room dim | | viewed crosswise | | | | | viewed endwise | | | | |
| x | y | | | | | | | | | | |
| 2H | 2H | -8.0 | -7.5 | -7.7 | -7.3 | -7.0 | -8.0 | -7.5 | -7.7 | -7.3 | -7.0 |
| | 3H | -8.1 | -7.7 | -7.8 | -7.4 | -7.1 | -8.1 | -7.7 | -7.8 | -7.4 | -7.1 |
| | 4H | -8.2 | -7.8 | -7.9 | -7.5 | -7.2 | -8.2 | -7.8 | -7.9 | -7.5 | -7.2 |
| | 6H | -8.3 | -7.9 | -7.9 | -7.6 | -7.2 | -8.3 | -7.9 | -7.9 | -7.6 | -7.3 |
| | 8H | -8.3 | -7.9 | -8.0 | -7.6 | -7.3 | -8.3 | -7.9 | -8.0 | -7.6 | -7.3 |
| | 12H | -8.3 | -8.0 | -8.0 | -7.6 | -7.3 | -8.4 | -8.0 | -8.0 | -7.7 | -7.3 |
| 4H | 2H | -8.2 | -7.8 | -7.9 | -7.5 | -7.2 | -8.2 | -7.8 | -7.9 | -7.5 | -7.2 |
| | 3H | -8.4 | -8.0 | -8.0 | -7.7 | -7.3 | -8.4 | -8.0 | -8.0 | -7.7 | -7.3 |
| | 4H | -8.5 | -8.1 | -8.1 | -7.8 | -7.4 | -8.5 | -8.1 | -8.1 | -7.8 | -7.4 |
| | 6H | -8.5 | -8.2 | -8.1 | -7.8 | -7.4 | -8.5 | -8.3 | -8.1 | -7.9 | -7.4 |
| | 8H | -8.6 | -8.3 | -8.1 | -7.9 | -7.5 | -8.6 | -8.3 | -8.1 | -7.9 | -7.5 |
| | 12H | -8.6 | -8.4 | -8.1 | -7.9 | -7.5 | -8.6 | -8.4 | -8.2 | -8.0 | -7.5 |
| 8H | 4H | -8.6 | -8.3 | -8.1 | -7.9 | -7.5 | -8.6 | -8.3 | -8.1 | -7.9 | -7.5 |
| | 6H | -8.7 | -8.4 | -8.2 | -8.0 | -7.5 | -8.7 | -8.4 | -8.2 | -8.0 | -7.5 |
| | 8H | -8.7 | -8.5 | -8.2 | -8.0 | -7.5 | -8.7 | -8.5 | -8.2 | -8.0 | -7.5 |
| | 12H | -8.7 | -8.6 | -8.2 | -8.1 | -7.6 | -8.7 | -8.6 | -8.2 | -8.1 | -7.6 |
| 12H | 4H | -8.6 | -8.4 | -8.2 | -8.0 | -7.5 | -8.6 | -8.4 | -8.1 | -7.9 | -7.5 |
| | 6H | -8.7 | -8.5 | -8.2 | -8.1 | -7.6 | -8.7 | -8.5 | -8.2 | -8.0 | -7.5 |
| | 8H | -8.7 | -8.6 | -8.2 | -8.1 | -7.6 | -8.7 | -8.6 | -8.2 | -8.1 | -7.6 |
| Variations with the observer position at spacing: | | | | | | | | | | | |
| S = | 1.0H | 6.7 / -11.6 | | | | | 6.7 / -11.6 | | | | |
| | 1.5H | 9.6 / -12.2 | | | | | 9.6 / -12.2 | | | | |
| | 2.0H | 11.5 / -12.6 | | | | | 11.5 / -12.6 | | | | |